

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;">SCHNEIDER FILTRU 3000 VA APC - MARINA</p> <p>Denumire model Filtru 3000 VA APC - Marina Include Ghid de instalare , Componente de montaj , Manual de utilizare Timp de livrare standard De obicei in stoc</p> <hr/> <p>Tensiune nominala la iesire 200V , 208V , 220V , 230V , 240V Consum de curent total maxim per faza 16 A Conexiuni de iesire (1) IEC 320 C19 (Battery Backup) Intotdeauna la prize 1 Protectie la suprasarcina Nu Lungime cablu 8 Tensiune nominala de intrare 208V - 220V - 230V - 240V Frecventa de intrare 47 - 63 Hz Curent de intrare redus regulat (America de Nord) 16 A Conexiuni de intrare IEC-320 C20 Lungime cablu 2.44 metri Numar de cabluri de alimentare 1 Acceptable Input Voltage 100-240 VAC Curent maxim de linie per faza 16 A Curent maxim de intrare per faza 16 A Capacitate sarcina 3000 VA Greutate neta 5.09 kg Inaltime maxima 44.0 mm Latime maxima 432.0 mm Adancime maxima 279.0 mm Greutate de transport 6.36 kg Inaltime transport 76.0 mm Latime de transport 381.0 mm Adancime transport 559.0 mm Culoare Negru Mediu de operare 0 - 55 °C Umiditate relativa de functionare 0 - 95 % Inaltime de operare 0-3000 metri Temperatura de depozitare -25 - 75 °C Umiditate relativa depozitare 0 - 95 % Inaltime depozitare 0-15000 metri Aprobari reglementare DNV Garantie standard 2 ani reparatii sau inlocuire Politica de protectie echipament -- RoHS (Restrictionarea substantelor periculoase) Conformatitate Regulament REACH REGULAMENT: Nu contine SVHC (Substante care prezinta motive de ingrijorare deosebita) Pret: 0,00 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/filtru-3000-va-apc-marina-100445</p>
---	---