

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410

	<p>SCHNEIDER MICROLOGIC 6.0 A UNITATE DE DECLANSARE - LSIG - PENTRU NW 08 - 63 DEBROSABIL</p> <p>gama Masterpact nume produs Micrologic tip produs sau componenta Unitate de cda compatibilitate gama Masterpact NW08...40 - Masterpact NW40b...63 - Masterpact NW H10 - Masterpact NW H2 corrosion protection domeniu de aplicare al aparatului Distribution descriere poli 4P - 3P descriere poli protejati 4t - 3t - 3t + N/2 tip retea C.a. frecventa retea 50/60 Hz nume unitate de declansare Micrologic 6.0 A tehnologie unitate de declansare Electronic functii de protectie a unitatii de declansare Selective + earth-fault protection tip de protectie Protectie instantanea la scurtcircuit - Earth fault - Protectie la suprasarcina (timpindelungat) - Protectie la scurtcircuit pe perioada scurta gama uitatii de declansare 800 A la 50 °C - 1000 A la 50 °C - 1250 A la 50 °C - 1600 A la 50 °C - 2000 A la 50 °C - 2500 A la 50 °C - 3200 A la 50 °C mod de montare Debrosabil tip de reglare a restabilitii prelungite Ir 9 setari reglabile interval de reglare a restabilitii prelungite 0,4...1 x In tip de ajustareintarziere prelungita 9 setari reglabile [tr] reglarea intarzierii de lunga durata 0,7...16,6 s 7.2 x Ir - 0,7...24 s 6 x Ir - 12,5...600 s 1.5 x Ir memorie termica 20 mn tip de reglare a restabilitii pe termen scurt lsd 9 setari reglabile [lsd] interval de reglare a restabilitii pe termen scurt 1,5...10 x Ir tip de ajustareintarziere scurta Reglabil [tsd] temporizare reglabilă 0...0,4 s $I^2t=off$ - 0,1...0,4 s $I^2t=on$ tip de reglare a restabilitii instantanea Ii Adjustable 9 settings interval de reglare a restabilitii instantanea 2...15 x In - Oprit tip de reglare a restabilitii dupa eroare de legare la pamant Adjustable 9 settings [Ig] ground-fault pick-up adjustment range 0,2...1 x In pentru 400 A < In < 1250 A - 0,3...1 x In pentru In = 1250 A tip de reglare aintarzierii dupa eroare de legare la pamant -tg Reglabil [tg] gama de reglaj a temporizarii protectiei homopolare 0...0,4 s $I^2t=off$ - 0,1...0,4 s $I^2t=on$ blocare ZSI cu selectare a zonei Cu comunicare a datelor Measurement readout - Setari de protectie si alarma tip afisaj Afisaj digital tip de masurare Ampermetru temperatura ambianta pentru utilizare -25...70 °C temperatura de depozitare -25...85 °C Stare oferta sustenabila Produs Green Premium Regulamentul REACH Declaratia REACH Directiva RoHS UE Not applicable, out of EU RoHS legal scope Fara mercur Da Informatii privind scutirea de la RoHS Da Regulamentul RoHS Declaratia RoHS Produs in afara domeniului de aplicare a RoHS . Declaratia privind substantele in scop informativ. Raport de mediu Profilul ambiental al produsului Profil circularitate Informatii privind sfarsitul duratei de viata Garantie 18 luni Pret: 6 187,62 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/micrologic-6-0-a-unitate-de-declansare-lsig-pentru-nw-08-63-debrosabil-100723</p>
---	---