

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**SCHNEIDER RACK PDU 2G, CONTORIZAT LA PRIZA, ZERO U, 16 A,
230 V, (21) C13 SI (3) C19**

Descriere APC Metered by Outlet Rack Power Distribution Units (PDUs) provide individual outlet power metering to enable energy optimization and circuit protection. Current metering provides real-time remote monitoring of connected loads. Metered by Outlet Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower total cost of ownership. Metered by Outlet Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra low profile circuit breakers. Users can access and configure Metered by Outlet Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.

Denumire model Rack PDU 2G, contorizat la priza, Zero U, 16 A, 230 V, (21) C13 si (3) C19

Include Terminatie port CAN , Ghid de instalare , Console de montare rack , Ghid de siguranta , Cablu de configurare sel

Timp de livrare standard De obicei in stoc

.....
Tensiune nominala la iesire 230V

Consum de curent total maxim per faza 16 A

Conexiuni de iesire (21) IEC 320 C13 (Battery Backup) , (3) IEC 320 C19 (Battery Backup)

Tensiune nominala de intrare 200V - 208V - 230V

Frecventa de intrare 50/60 Hz

Conexiuni de intrare IEC 309 16A 2P+E

Lungime cablu 3 metri

Acceptable Input Voltage 100-240 VAC

Curent maxim de intrare per faza 16 A

Capacitate sarcina 3700 VA

Greutate neta 6.76 kg

Inaltime maxima 1829.0 mm

Latime maxima 56.0 mm

Adancime maxima 51.0 mm

Greutate de transport 9.03 kg

Inaltime transport 2037.0 mm

Latime de transport 163.0 mm

Adancime transport 117.0 mm

Culoare Negru

Mediu de operare -5 - 45 °C

Umiditate relativa de functionare 5 - 95 %

Inaltime de operare 0-3000 metri

Temperatura de depozitare -25 - 65 °C

Umiditate relativa depozitare 5 - 95 %

Inaltime depozitare 0-15000 metri

Aprobari reglementare EN 55022 Clasa A , EN 55024 , EN 61000-3-2 , EN 61000-3-3 , FCC Partea 15 Clasa A , ICES-003 , Listat UL , VCCI Catego A , VDE

Garantie standard 2 ani reparatii sau inlocuire

RoHS (Restrictionarea substantelor periculoase) Conformitate

Regulament REACH REGULAMENT: Nu contine SVHC (Substante care prezinta motive de ingrijorare deosebita)

Directiva baterie Conformitate

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/rack-pdu-2g-contorizat-la-priza-zero-u-16-a-230-v-21-c13-si-3-c19-101861>