

	<u>SCHNEIDER APC SMART-UPS X 2200VA RACK/TOWER LCD 200-240V WITH NETWORK CARD</u> Denumire model APC Smart-UPS X 2200VA Rack/Tower LCD 200-240V with Network Card Include CD cu software , Documentatie pe CD , Ghid de instalare , Placa de gestionare retea , Sine de susținere pentru montare rack , Cablu RS-232 semnalizare Smart UPS , Sonda de temperatura , Cablu USB Timp de livrare standard De obicei in stoc Capacitate putere de iesire 1980 Wati / 2200 VA Putere max. configurabila (wati) 1980 Wati / 2200 VA Tensiune nominala la iesire 208V , 230V Distorsiune tensiune de iesire Sub 5% Frecventa de iesire (sincronizata cu alimentarea de la retea) 50/60Hz +/- 3 Hz Alte tensiuni de iesire 220, 240V Linie interactiva Tip forma de unda Unda sinusoidala Conexiuni de iesire (1) IEC 320 C19 (Battery Backup) , (2) IEC Jumpers (Battery Backup) , (8) IEC 320 C13 (Battery Backup) Tensiune nominala de intrare 208V - 230V Frecventa de intrare 50/60 Hz +/- 3 Hz (detectare automata) Conexiuni de intrare British BS1363A , IEC-320 C20 , Schuko CEE 7/EU1-16P Lungime cablu 1.83 metri Interval tensiune de intrare pentru operatii principale 140 - 280 V Alte tensiuni la intrare 220 , 240 Tip de acumulator Baterie cu placi de plumb si acid, etanșă™ ata, care nu necesita intretinere, cu electrolit suspendat: etans Timp de reincarcare tipic 3 ora(ore) Replacement Battery APCRBC117 Cantitate RBC™ 1 Port(uri) interfata RJ-45 10/100 Base-T , Sel RJ-45 , SmartSlot , USB Carduri SmartSlot™ preinstalate AP9631 Panou de cda Afisare stare cu LED cu grafice cu bare privind sarcina si bate si indicatoare on line: Pe baterie: Inlocuire baterie: si indicatoare de suprasarcina , Consola de cda si stare LCD multifunctional Alarma sonora Alarma cand functioneaza pe baterie: alarma distincta pentru baterie descarcata: intarzieri configurabile Intrerupere de urgenta a alimentarii (EPO) Yes Capacitate nominala supratensiune 645 Jouli Filtrare Filtrare multipolara zgomot, cu functionare continua: 0,3% Limitare supratensiune IEEE: timp de raspuns prindere zero : conform standardului UL 1449 Inaltime maxima 85.0 mm Latime maxima 432.0 mm Adancime maxima 667.0 mm Inaltime rack 2 U Greutate neta 37.24 kg Greutate de transport 45.26 kg Inaltime transport 243.0 mm Latime de transport 596.0 mm Adancime transport 869.0 mm Culoare Negru Unitati per palet 8.0 # straturi per palet 4 # unitati per strat per palet 2 Greutate palet 387.88 kg Mediu de operare 0 - 40 °C Umiditate relativa de functionare 0 - 95 % Inaltime de operare 0-3000 metri Temperatura de depozitare -15 - 45 °C Umiditate relativa depozitare 0 - 95 % Inaltime depozitare 0-15000 metri Zgomot sonor la 1 metru de suprafata unitatii 55.000 dB Pierdere termica online 150.000 BTU/h Aprobari reglementare CE , CSA , EAC , EN/IEC 62040-1 , EN/IEC 62040-2 , FCC Partea 15 Clasa A , IEC 60950 , IRAM , RCM , UL 1778 , VDE Garantie standard 3 ani reparatii sau inlocuire (exceptand bate) si 2 ani pentru baterie RoHS (Restrictionarea substantelor periculoase) Conformitate Regulament REACH REGULAMENT: Nu contine SVHC (Substante care prezinta motive de ingrijorare deosebita) Directiva baterie Conformitate Pret: 0,00 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/apc-smart-ups-x-2200va-rack-tower-lcd-200-240v-with-network-card-102307
--	---