

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410

	<b>SCHNEIDER APC SMART-UPS SRT 1500VA RM 230V</b>  Denumire model APC Smart-UPS SRT 1500VA RM 230V Include CD cu software , Comms cable , Documentatie pe CD , Ghid de instalare , Console de montare rack , Sine de susținere pentru montare rack , Componente de montare rack , Cablu USB , Carnet de garantie Timp de livrare standard De obicei in stoc  Capacitate putere de iesire 1500 Watt / 1500 VA Putere max. configurabila (watt) 1500 Watt / 1500 VA Tensiune nominala la iesire 230V Distorsione tensiune de iesire Sub 2% Frecventa de iesire (sincronizata cu alimentarea de la retea) 50/60Hz +/- 3 Hz Alte tensiuni de iesire 220, 240V Factor de varf 3 : 1 Online cu dubla conversie Tip forma de unda Unda sinusoidală Conexiuni de iesire (6) IEC 320 C13 (Battery Backup) Derivatie Bypass incorporat Tensiune nominala de intrare 230V Frecventa de intrare 40 - 70 Hz (detectare automata) Conexiuni de intrare IEC-320 C14 Lungime cablu 1.83 metri Interval tensiune de intrare pentru operatii principale 50-150 (40% Load) V , 80 - 150 V Alte tensiuni la intrare 220 , 240 Tip de acumulator Baterie cu placi de plumb si acid, etanșata, care nu necesita intretinere, cu electrolit suspendat: etans Module baterie incluse 1 Timp de reincarcare tipic 3 ora(ore) Replacement Battery APCRBC155 Cantitate RBC™ 1 Port(uri) interfata Sel RJ-45 , Smart-Slot , USB Calitate interfata SmartSlot™ disponibila 1 Panou de cda Consola de cda si stare LCD multifunctional Alarma sonora Alarme sonore si vizibile prioritizate dupa gravitate Intrerupere de urgență a alimentarii (EPO) Yes Capacitate nominala supratensiune 432 Jouli Inaltime maxima 85.0 mm Latime maxima 432.0 mm Adancime maxima 505.0 mm Inaltime rack 2 U Greutate neta 21.0 kg Greutate de transport 29.6 kg Inaltime transport 246.0 mm Latime de transport 594.0 mm Adancime transport 749.0 mm Culoare Negru Unitati per palet 12.0 Mediu de operare 0 - 40 °C Umiditate relativa de functionare 0 - 95 (non-condensing) % Inaltime de operare 0-3000 metri Temperatura de depozitare -20 - 50 °C Umiditate relativa depozitare 0 - 95 (non-condensing) % Inaltime depozitare 0-15000 metri Zgomot sonor la 1 metru de suprafata unitatii 50.000 dB Pierdere termica online 317.000 BTU/h Clasa de protectie IP 20 Aprobari reglementare CE , EAC Garantie standard 3 ani reparatii sau inlocuire (exceptand baterie) si 2 ani pentru baterie RoHS (Restrictionarea substanelor periculoase) Conformitate Pret: 0,00 lei (TVA inclus)  Detalii online: <a href="https://www.materialelectrice.ro/apc-smart-ups-srt-1500va-rm-230v-102378">https://www.materialelectrice.ro/apc-smart-ups-srt-1500va-rm-230v-102378</a>
---	--