

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER CONTROLER MOTOR LTM R TESYS T - 24 V C.C. 8 A PENTRU CANOPEN

gama TeSys
nume produs TeSys T
nume scurt al dispozitivului LTMR
tip produs sau componenta Controler motor
domeniul de aplicare al aparatului Equipment monitoring and control
curentul de masura 0,4...8 A
[Us] tensiune nominala de alimentare 24 V c.c.
curentul consumat 56...127 mA
limitele tensiunii de alimentare 20,4...26,24 V c.c.
protocol port de comunicare CANopen
tip magistrala CANopen ISO 1198 interfata, adresare 1...127, rata de transmisie 10...1000 kbit/s, SUB-D 9 cu 4 twisted shielded pairs cable - CANopen ISO 1198 interfata, adresare 1...127, rata de transmisie 10...1000 kbit/s, cutie de borne cu 4 twisted shielded pairs cable
[Ui] tensiune nominala de izolare 690 V conformitate cu EN/IEC 60947-1 - 690 V conformitate cu CSA C22.2 No 15 - 690 V conformitate cu UL 508
[Uimp] tensiune de tinere la impuls 6 kV current or voltage measurement circuit conformitate cu EN/IEC 60947-4-1 - 0,8 kV communication circuit conformitate cu EN/IEC 60947-4-1 - 0,8 kV supply, inputs and outputs conformitate cu EN/IEC 60947-4-1 incercare la scurtcircuit 100 kA conformitate cu EN/IEC 60947-4-1
calibrul fuzibilului asociat 4 A gG pentru iesire - 0,5 A gG pentru circuit de cda
tip de protectie Overload (long time) - Defect faza - Load fluctuation - Phase imbalance - Protectie fata de polaritate inversa - Protectie termica - Protectie la suprasarcina termica - Protectie de scurgere la pamant - Power factor vation - Overload - Locked rotor network and machine diagnosis type Trip context information - Remaining operating time before overload tripping - Starting current and time - Event recording - Motor control command recording - Running hours counter/operating time - Waiting time after overload tripping - Trip history information - Phase fault and earth fault trip counters - Fault recording
numar de intrare logica 6
curent de intrare 7 mA
stare curenta 0 garantata Logic input < 5 V si 0.1 A) - 1 % tensiune (100...830 V) - 3 % factor de putere (cos φ > 0.6) - 5 % earth fault current external measurement (< 5 % or 0.01 A) - +/- 30 min/year internal clock - 0,02 temperature - 1 % curent - 5 % active and reactive power
categorii de supratensiune III
pasul conexiunii 5,08 mm
conexiuni - borne Circuit de cda conector 1 cablu(ri) 0,25...2,5 mm² (AWG 24 - AWG 14)flexibil cu - Circuit de cda conector 1 cablu(ri) 0,2...2,5 mm² (AWG 24 - AWG 14)flexibil fara - Circuit de cda conector 1 cablu(ri) 0,25...2,5 mm² (AWG 24 - AWG 14)flexibil fara - Circuit de cda conector 1 cablu(ri) 0,2...2,5 mm² (AWG 24 - AWG 14)solid fara - Circuit de cda conector 2 cablu(ri) 0,2...1 mm² (AWG 24 - AWG 14)flexibil cu - Circuit de cda conector 2 cablu(ri) 0,2...1,5 mm² (AWG 24 - AWG 14)flexibil fara - Circuit de cda conector 2 cablu(ri) 0,5...1,5 mm² (AWG 24 - AWG 14)flexibil fara - Circuit de cda conector 2 cablu(ri) 0,2...1 mm² (AWG 24 - AWG 14)solid fara
cuplu de strangere Circuit de cda 0,5...0,6 N.m plat surubelnita 3 mm
grad de poluare 3
compatibilitate electromagnetica Descarcare electrostatica, 3 (8 kV air, 6 kV contact) (EN/IEC 61000-4-2) - Campuri RF radiate, 3 (10 V/m) (EN/IEC 61000-4-3) - Test de imunitate la tranzienti rapizi, nivel 3 (2 kV) (EN/IEC 61000-4-4) - Test de imunitate la tranzienti rapizi, level 4 (4 kV) (EN/IEC 61000-4-4) - Test de imunitate la caderi de tensiune si intreruperi (70 %, 500 ms) (EN/IEC 61000-4-11) - Perturbatii conduse de RF (10 V) (EN/IEC 61000-4-6) - Supratensiuni tranzitorii (0.5 kV) (EN/IEC 61000-4-5) - Supratensiuni tranzitorii (1 kV) (EN/IEC 61000-4-5) - Supratensiuni tranzitorii (1 kV) (EN/IEC 61000-4-5) - Supratensiuni tranzitorii (1 kV) (EN/IEC 61000-4-5) - Supratensiuni tranzitorii (2 kV) (EN/IEC 61000-4-5) - Supratensiuni tranzitorii (2 kV) (EN/IEC 61000-4-5) - Supratensiuni tranzitorii (4 kV) (EN/IEC 61000-4-5)
latime 91 mm
inaltime 61 mm
adancime 122,5 mm
greutate produs 0,53 kg
servicii Web Server web
Cod compatibilitate LTMR
standarde SR EN 60947-4-1 - CSA C22.2 No 15 - IEC 60947-4-1 - UL 508 - IACS E10 certificari produs ATEX - C-Tick - EAC - LROS (Lloyds register of shipping) - NOM - BV - RINA - KERI - ABS - UL - CSA - DNV - RMRoS - GL - CCC
tratament protector 12 x 24 hour cycles conformitate cu EN/IEC 60068-2-30 - 48 h conformitate cu EN/IEC 60070-2-11 - TH conformitate cu EN/IEC 60068
rezistenta la foc 650 °C conformitate cu EN/IEC 60695-2-12 - 960 °C conformitate cu UL 94
temperatura de utilizare -20...60 °C
temperatura de depozitare -40...80 °C
altitudinea de functionare Stare oferta sustenabila Produs Green Premium
Regulamentul REACH Declaratia REACH
Directiva RoHS UE Under investigation
Fara mercur Da

	Informatii privind scutirea de la RoHS Da Regulamentul RoHS Declaratia RoHS Produs in afara domeniului de aplicare a RoHS . Declaratia privind substantele in scop informativ. Raport de mediu Profilul ambiental al produsului Profil circularitate Informatii privind sfarsitul duratei de viata WEEE In Uniunea Europeana, produsele trebuie reciclate respectand sistemul specific de colectare a deseurilor si nu trebuie sa ajunga in pubelele de colectare a deseurilor menajere. Garantie 18 luni Pret: 2 591,73 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/controler-motor-ltm-r-tesys-t-24-v-c-c-8-a-pentru-canopen-103813
--	---