


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO H-DISTRIBUTION CONNECTOR; 2-POLE; COD. B; 1 INPUT; 2
OUTPUTS; OUTPUTS ON BOTH SIDES; 3 LOCKING LEVERS; FOR
FLYING LEADS; GRAY**

Note on Contact Resistance: approx. 1 mΩ; of contact resistanceâ€© approx. 0.25 mΩ; contact transition plug/socket;
Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 250; V
Tensiune nominala de supratensiune (III/3): 4; kV
Curent nominal: 25; A
Legend (ratings): (III / 3) â‰‰™ Overvoltage category III / Pollution degree 3;
Tensiune nominala UL 1977: 600; V
Curent nominal UL 1977: 23; A
Numar poli: 2;
Total number of potentials: 2;
Distanta intre pini: 10 mm / 0.394 inch;
Latime: 20 mm / 0.787 inch;
Inaltime: 32,7 mm / 1.287 inch;
Adancime: 51 mm / 2.008 inch;
Coding: B;
Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);
Retention force of a plug-in connection: When locked: > 80 N;
Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);
Number of mating cycles: î»¿200, without resistive load 100, with resistive load IN = 25 A, tested (4 mm²/AWG 12);
Distributor type: h-distribution connector (bi-directional);
Marking: 1 2;
Protection type: IP20;
Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;
Potential marking: 1 2;
Suitable: for flying leads;
Tip contact (pluggable connector): Socket/plug;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: yes;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Contact material: Copper or copper alloy (surface-treated);
Greutate: 14,8; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: Insulating parts for temperatures ≤ 105 °C;
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143561822;
Customs tariff number: 85366990990;
Pret: 25,49 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/h-distribution-connector-2-pole-cod-b-1-input-2-outputs-outputs-on-both-sides-3-locking-levers-for-flying-leads-gray-131338>