

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



WAGO PRE-ASSEMBLED CONNECTING CABLE; ECA; PLUG/OPEN-ENDED; 3-POLE; COD. A/S; 3 M; 1.50 MM²; BLACK/BROWN

Note on Contact Resistance: approx. 1 mΩ; of contact resistance ≈ approx. 0.25 mΩ;
 contact transition plug/socket;
 Ratings per: IEC/EN 60664-1;
 Tensiune nominala (III/3): 250; V
 Tensiune nominala de supratensiune (III/3): 4; kV
 Current nominal: 16; A
 Legend (ratings): (III / 3) %™ Overvoltage category III / Pollution degree 3;
 Tensiune nominala UL 1977: 600; V
 Current nominal UL 1977: 23; A
 Number of poles: 3;
 Total number of potentials: 3;
 Conductor preparation: tip-bonded;
 Sheathed cable diameter: 7,4 ... 9,4 mm;
 Cross-sectional area of the conductor: 1,5; mm²
 Connection type: Plug; Plug - Free end;
 Distance between pins: 10 mm / 0.394 inch;
 Total length: 3; m
 Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);
 Retention force of a plug-in connection: when locked: > 80N;
 Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);
 Number of mating cycles: 200 (without resistive load) 100 (with resistive load IN = 25 A), tested (4 mm²);
 Connection type: Plug; Plug - Free end;
 Type of pre-assembled cable: Connecting cable;
 Cable type: H05Z1Z1-F 3x1.5;
 Protection type: IP20;
 Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;
 Suitable for: for distribution connectors (770-637 and 770-687);
 Mismatching protection: Yes;
 Locking of plug-in connection: locking lever;
 Locking lever: retrofittable;
 Color: black/brown;
 Material of insulation: Polyamide 66 (PA 66);
 Fire class per EN 50575: Eca;
 Contact material: Copper or copper alloy (surface-treated);
 Fire load: 3,569; MJ
 Halogen-free: Yes;
 Grease: 301; g
 Processing temperature: -5 ... +40 °C;
 Continuous operating temperature: -35 ... +85 °C;
 Note on continuous operating temperature: PVC cable for temperatures ≤ 70 °C (including halogen-free) Insulating parts for temperatures ≤ 105 °C;
 Tip marking: not packed;
 Origin: DE;
 GTIN: 4050821698258;
 Customs tariff number: 85444290900;
 Price: 115.59 lei (TVA included)

Detalii online: <https://www.materialeelectrice.ro/pre-assembled-connecting-cable-eca-plug-open-ended-3-pole-cod-a-s-3-m-1-50-mm2-black-brown-132004>