

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO 4-CONDUCTOR MODULAR PCB CONNECTOR; FOR
INDIVIDUAL SOLDER PINS; 0.8 MM $\bar{A}$; PIN SPACING 5.75 MM; 1-
POLE; DARK GRAY**

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 250; V
Tensiune nominala de supratensiune (III/3): 4; kV
Tensiune nominala (III/2): 320; V
Tensiune nominala de supratensiune (III/2): 4; kV
Tensiune nominala (II/2): 630; V
Tensiune nominala de supratensiune (II/2): 4; kV
Curent nominal: 6; A
Legend (ratings): (III / 2) $\hat{A}\%$ ™ Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group B): 150; V
Curent nominal UL (Use Group B): 7; A
Tensiune nominala UL (Use Group D): 150; V
Curent nominal UL (Use Group D): 7; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group B): 150; V
Curent nominal CSA (Use Group B): 7; A
Tensiune nominala CSA (Use Group D): 150; V
Curent nominal CSA (Use Group D): 7; A
Tehnologie conexiune: PUSH WIRE®;
Connectable conductor materials: Copper;
Solid conductor: 0,5 ... 1 mm² / 24 ... 18 AWG;
Conductor diameter: 0,5 ... 1 mm;
Strip length: 5 ... 6 mm / 0.2 ... 0.24 inch;
Conductor connection direction to PCB: 0; °
Numar poli: 1;
Numar total de conexiuni: 4;
Total number of potentials: 1;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 5,75 mm / 0.226 inch;
Latime: 5,75 mm / 0.226 inch;
Inaltime: 10 mm / 0.394 inch;
Adancime: 10,5 mm / 0.413 inch;
Lungimea pinului de contact: 4,5; mm
Diametrul pinului de contact: 1; mm
Diametrul de gaurire cu toleranta: 1,2 (-0,05 ... +0,05) mm;
Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for PCBs;
Mating direction to the PCB: 90; °
PCB contact: THT;
Culoare: dark gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Copper alloy;
Contact material: Cupru electrolitic (ECu);
Contact plating: tin-plated;
Greutate: 0,8; g
Temperatura lucru: -60 ... +105 °C;
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143467407;
Customs tariff number: 85369010000;
Pret: 1,13 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-conductor-modular-pcb-connector-for-individual-solder-pins-0-8-mm-oe-pin-spacing-5-75-mm-1-pole-dark-gray-132280>