


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>WAGO THT MALE HEADER; 1.0 MM $\tilde{\sim}$ SOLDER PIN; ANGLED; CLAMPING COLLAR; PIN SPACING 3.5 MM; 8-POLE; LIGHT GRAY</u> Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 160; V Tensiune nominala de supratensiune (III/3): 2,5; kV Tensiune nominala (III/2): 160; V Tensiune nominala de supratensiune (III/2): 2,5; kV Tensiune nominala (II/2): 320; V Tensiune nominala de supratensiune (II/2): 2,5; kV Curent nominal: 10; A Legend (ratings): (III / 2) $\hat{\sim}$™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 10; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Numar poli: 8; Total number of potentials: 8; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 3,5 mm / 0.138 inch; Latime: 30 mm / 1.181 inch; Inaltime: 16 mm / 0.63 inch; Inaltime de la fata: 12,4 mm / 0.488 inch; Adancime: 17,5 mm / 0.689 inch; Lungimea pinului de contact: 3,6; mm Diametrul pinului de contact: 1; mm Diametrul de gaurire cu toleranta: 1,2 (+0,1) mm; Tip montaj: Mounting flange; Tip montaj: Feed-through mounting; Panel mounting; Tip contact (pluggable connector): Conector tata/fisa; Connector (connection type): for PCB; Mismatching protection: No; Mating direction to the PCB: 0; ° Locking of plug-in connection: Locking latch; PCB contact: THT; Culoare: light gray; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Contact material: Cupru electrolitic (ECu); Contact plating: tin-plated; Fire load: 0,072; MJ Greutate: 3,3; g Temperatura lucru: -60 ... +100 °C; Tip ambalare: BOX; Tara de origine: DE; GTIN: 4050821412021; Customs tariff number: 85366990990; Pret: 10,93 lei (TVA inclus) Detalii online: https://www.materialelectrice.ro/tht-male-header-1-0-mm-oe-solder-pin-angled-clamping-collar-pin-spacing-3-5-mm-8-pole-light-gray-133025
--	--