

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

Hole pattern 2 solder pins/pole in line 4-pole 	<u>WAGO PCB TERMINAL BLOCK; PUSH-BUTTON; 1.5 MM²; PIN SPACING 5 MM; 6-POLE; PUSH WIRE[®]; 1,50 MM²; GRAY</u> Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 320; V Tensiune nominala de supratensiune (III/3): 4; kV Tensiune nominala (III/2): 320; V Tensiune nominala de supratensiune (III/2): 4; kV Tensiune nominala (II/2): 630; V Tensiune nominala de supratensiune (II/2): 4; kV Curent nominal: 10; A Legend (ratings): (III / 2) %TM Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 10; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Tensiune nominala CSA (Use Group B): 300; V Curent nominal CSA (Use Group B): 10; A Tensiune nominala CSA (Use Group D): 300; V Curent nominal CSA (Use Group D): 10; A Tehnologie conexiune: PUSH WIRE[®]; Tip actionare: Push-button; Solid conductor: 0.5 ... 1.5 mm² / 20 ... 16 AWG; Fine-stranded conductor; with insulated ferrule: 0.5 ... 1 mm²; Fine-stranded conductor; with uninsulated ferrule: 0.5 ... 1 mm²; Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch; Conductor connection direction to PCB: 90; ° Numar poli: 4; Numar total de conexiuni: 4; Total number of potentials: 4; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 5 mm / 0.197 inch; Latime: 30 mm / 1.181 inch; Inaltime: 19.4 mm / 0.764 inch; Inaltime de la fata: 15.9 mm / 0.626 inch; Adancime: 10.8 mm / 0.425 inch; Lungimea pinului de contact: 3,5; mm Solder pin dimensions: 0.4 x 0.9 mm; Diametrul de gaurire cu toleranta: 1 (+0.1) mm; PCB contact: THT; Solder pin arrangement: over the entire terminal strip, in line; Number of solder pins per potential: 2; Culoare: gray; Material group: I; Material izolator: Polyamide 66 (PA 66); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Cupru electrolitic(ECu); Contact plating: tin-plated; Fire load: 0,068; MJ Greutate: 3,9; g Temperatura lucru: -60 ... +105 °C; Product Group: 4 (Printed Circuit); Tip ambalare: BOX; Tara de origine: CH; GTIN: 4044918793148; Customs tariff number: 85369010000; Pret: 6,15 lei (TVA inclus) Detalii online: https://www.materialelectrice.ro/pcb-terminal-block-push-button-1-5-mm2-pin-spacing-5-mm-6-pole-push-wire-1-50-mm2-gray-133193
---	--