

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>WAGO PRE-ASSEMBLED INTERCONNECTING CABLE; ECA; SOCKET/PLUG; 5-POLE; COD. B; 5 M; 1,50 MM²; GRAY</u> Note on Contact Resistance: approx. 1 mΩ; of contact resistance ≈ approx. 0.25 mΩ; contact transition plug/socket; Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 400; V Tensiune nominala de supratensiune (III/3): 6; kV Curent nominal: 16; A Note on Curent nominal: 13 A for 3-pole load 10 A for 4- and 5-pole load; Legend (ratings): (III / 3) %™ Overvoltage category III / Pollution degree 3; Tensiune nominala UL 1977: 600; V Curent nominal UL 1977: 12; A Numar poli: 5; Total number of potentials: 5; Conductor preparation: tip-bonded; Sheathed cable diameter: 9,3 ... 11,6 mm; Sectiunea transversala a firului: 1,5; mm² Connection type: Socket - Plug; Distanța între pini: 4,4 mm / 0.173 inch; Total length: 5; m Coding: B; Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number); Retention force of a plug-in connection: when locked: > 80N; Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number); Number of mating cycles: ≥200, without resistive load 100, with resistive load IN = 16 A, tested (1.5 mm²/16 AWG); Connection type: Socket - Plug; Type of pre-assembled cable: Interconnecting cable; Cable type: Control line 5 x 1.5; Marking: 1 2 3 4 5; Protection type: IP20; Note on protection type: IP40 when mated; Potential marking: 1 2 3 4 5; Mismating protection: Yes; Locking of plug-in connection: locking lever; Locking lever: retrofittable; Culoare: gray; Material izolator: Polyamide 66 (PA 66); Fire class per EN 50575: Eca; Contact material: Copper or copper alloy (surface-treated); Connector Culoare: gray; Printing color of mating face: black; Strain relief Culoare: black; Printing color of strain relief: white; Sheathed cable Culoare: gray; Printing color of sheathed cable: black; Sheath material: PVC; Greutate: 842,6; g Processing temperature: -5 ... +40 °C; Continuous operating temperature: -35 ... +85 °C; Note on continuous operating temperature: PVC cable for temperatures ≤ 70 °C (including halogen-free) Insulating parts for temperatures ≤ 105 °C; Tip ambalare: not packed; Tara de origine: PL; GTIN: 4055143518369; Customs tariff number: 85444290900; Pret: 131,48 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/pre-assembled-interconnecting-cable-eca-socket-plug-5-pole-cod-b-5-m-1-50-mm2-gray-133752
---	---