


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>WAGO TRIPLE-DECK PCB TERMINAL BLOCK; 2.5 MM²; PIN SPACING 10.16 MM; 3 X 4-POLE; CAGE CLAMP®; 2,50 MM²; ORANGE</u> Ratings per: IEC/EN 60664-1; Ratings (note): between the modules; Tensiune nominala (III/3): 630; V Tensiune nominala de supratensiune (III/3): 8; kV Tensiune nominala (III/2): 1000; V Tensiune nominala de supratensiune (III/2): 8; kV Tensiune nominala (II/2): 1000; V Tensiune nominala de supratensiune (II/2): 8; kV Curent nominal: 21; A Ratings per: IEC/EN 60664-1; Ratings (note) 2: between the decks; Tensiune nominala (III/3) 2: 320; V Tensiune nominala de supratensiune (III/3) 2: 4; kV Tensiune nominala (III/2) 2: 320; V Tensiune nominala de supratensiune (III/2) 2: 4; kV Tensiune nominala (II/2) 2: 630; V Tensiune nominala de supratensiune (II/2) 2: 4; kV Curent nominal 2: 21; A Legend (ratings): (III / 2) %™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 10; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Tensiune nominala CSA (Use Group B): 300; V Curent nominal CSA (Use Group B): 10; A Tensiune nominala CSA (Use Group D): 300; V Curent nominal CSA (Use Group D): 10; A Tehnologie conexiune: CAGE CLAMP®; Tip actionare: Operating tool; Solid conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG; Fine-stranded conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG; Fine-stranded conductor; with insulated ferrule: 0,25 ... 1,5 mm²; Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 2,5 mm²; Strip length: 5 ... 6 mm / 0.2 ... 0.24 inch; Conductor connection direction to PCB: 45; ° Numar poli: 4; Numar total de conexiuni: 12; Total number of potentials: 12; Numar tipuri de conexiuni: 1; Numar nivele: 3; Note (conductor cross-section): 12 AWG: THHN, THWN; Distanta intre pini: 10,16 mm / 0.4 inch; Latime: 36,48 mm / 1.436 inch; Inaltime: 44 mm / 1.732 inch; Inaltime de la fata: 40 mm / 1.575 inch; Adancime: 31 mm / 1.22 inch; Lungimea pinului de contact: 4; mm Solder pin dimensions: 0,7 x 0,7 mm; Diametrul de gaurire cu toleranta: 1,3 (+0,1) mm; PCB contact: THT; Solder pin arrangement: within the terminal block (in-line); Number of solder pins per potential: 1; Culoare: orange; Material group: I; Material izolator: Polyamide 66 (PA 66); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Cupru electrolitic (ECu); Contact plating: tin-plated; Fire load: 0,38; MJ Greutate: 21; g Temperatura lucru: -60 ... +105 °C; Product Group: 4 (Printed Circuit); Tip ambalare: BOX; Tara de origine: PL; GTIN: 4045454022525; Customs tariff number: 85369010000; Pret: 35,05 lei (TVA inclus) Detalii online: https://www.materialelectrice.ro/triple-deck-pcb-terminal-block-2-5-mm2-pin-spacing-10-16-mm-3-x-4-pole-cage-clamp-2-50-mm2-orange-133753
---	--