

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>WAGO PRE-ASSEMBLED CONNECTING CABLE; ECA; PLUG/OPEN-ENDED; 4-POLE; COD. B; CONTROL CABLE 4 X 1.5 MM²; 3 M; 1,50 MM²; LIGHT GREEN</u> Note on Contact Resistance: approx. 1 mΩ; of contact resistanceâ€© approx. 0.25 mΩ; contact transition plug/socket; Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 400; V Tensiune nominala de supratensiune (III/3): 6; kV Curent nominal: 16; A Note on Curent nominal: 13 A for 3-pole load 10 A for 4-pole load; Legend (ratings): (III / 3) â‰‰™ Overvoltage category III / Pollution degree 3; Tensiune nominala UL 1977: 600; V Curent nominal UL 1977: 12; A Numar poli: 4; Total number of potentials: 4; Conductor preparation: tip-bonded; Sheathed cable diameter: 8,4 ... 10,5 mm; Sectiunea transversala a firului: 1,5; mm² Strip length (outer insulation): 38; mm Connection type: Plug - Free end; Distaanta intre pini: 4,4 mm / 0.173 inch; Total length: 3; m Coding: B; Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number); Retention force of a plug-in connection: when locked: > 80N; Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number); Number of mating cycles: î»¿200, without resistive load100, with resistive load IN = 16 A, tested (1.5 mm²/16 AWG); Connection type: Plug - Free end; Type of pre-assembled cable: Connecting cable; Cable type: Control line 4 x 1.5; Marking: 1 2 3 4; Protection type: IP20; Note on protection type: IP40 when mated; Potential marking: 1 2 3 4; Mismating protection: Yes; Locking of plug-in connection: locking lever; Locking lever: retrofittable; Culoare: light green; Material izolator: Polyamide 66 (PA 66); Fire class per EN 50575: Eca; Contact material: Copper or copper alloy (surface-treated); Fire load: 4,831; MJ Connector Culoare: light green; Printing color of mating face: black; Strain relief Culoare: black; Printing color of strain relief: white; Sheathed cable Culoare: gray; Printing color of sheathed cable: black; Sheath material: PVC; Greutate: 335,5; g Processing temperature: -5 ... +40 °C; Continuous operating temperature: -35 ... +85 °C; Note on continuous operating temperature: PVC cable for temperatures ≤ 70 °C (including halogen-free) Insulating parts for temperatures ≤ 105 °C; Tip ambalare: not packed; Tara de origine: PL; GTIN: 4050821682875; Customs tariff number: 85444290900; Pret: 72,98 lei (TVA inclus) Detalii online: https://www.materialelectrice.ro/pre-assembled-connecting-cable-eca-plug-open-ended-4-pole-cod-b-control-cable-4-x-1-5-mm2-3-m-1-50-mm2-light-green-133942
---	--