

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



WAGO PRE-ASSEMBLED CONNECTING CABLE; ECA; SOCKET/OPEN-ENDED; 4-POLE; COD. A; H05Z1Z1-F 4G 1.5 MM²; 7 M; 1,50 MM²; WHITE

Note on Contact Resistance: approx. 1 mΩ; of contact resistanceâ€© approx. 0.25 mΩ; contact transition plug/socket;
Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 400; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 16; A
Legend (ratings): (III / 3) â‰‰™ Overvoltage category III / Pollution degree 3;
Tensiune nominala UL 1977: 600; V
Curent nominal UL 1977: 12; A
Strip length: 9 mm / 0.35 inch;
Numar poli: 4;
Total number of potentials: 4;
Ground function: with preceding ground contact;
Conductor preparation: tip-bonded;
Sheathed cable diameter: 8,4 ... 10,5 mm;
Sectiunea transversala a firului: 1,5; mm²
Strip length (outer insulation): 45; mm
Connection type: Socket - Free end;
Distanta intre pini: 4,4 mm / 0.173 inch;
Total length: 7; m
Coding: A;
Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);
Retention force of a plug-in connection: when locked: > 80N;
Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);
Number of mating cycles: î»¿200, without resistive load100, with resistive load IN = 16 A, tested (1.5mm²/AWG 16);
Connection type: Socket - free end;
Type of pre-assembled cable: Connecting cable;
Cable type: H05Z1Z1-F 4G1.5;
Marking: N â€š 2/L 1/L';
Protection type: IP40;
Potential marking: N â€š 2/L 1/L';
Application: General mains applications;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: retrofittable;
Culoare: white;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: Eca;
Contact material: Copper or copper alloy (surface-treated);
Fire load: 12,846; MJ
Connector Culoare: white;
Printing color of mating face: black;
Strain relief Culoare: white;
Printing color of strain relief: black;
Sheathed cable Culoare: white;
Printing color of sheathed cable: black;
Halogen-free: Yes;
Greutate: 838,5; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ≤ 70 °C (including halogen-free) Insulating parts for temperatures ≤ 105 °C;
Tip ambalare: not packed;
Tara de origine: PL;
GTIN: 4055143405423;
Customs tariff number: 85444290900;
Pret: 132,04 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pre-assembled-connecting-cable-eca-socket-open-ended-4-pole-cod-a-h05z1z1-f-4g-1-5-mm2-7-m-1-50-mm2-white-134028>