


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>WAGO 1-CONDUCTOR FEMALE PLUG; 100% PROTECTED AGAINST MISMATING; PUSH-BUTTON; CLAMPING COLLAR; 1.5 MM²; PIN SPACING 3.5 MM; 18-POLE; 1.50 MM²; LIGHT GRAY</u> Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 160; V Tensiune nominala de supratensiune (III/3): 2,5; kV Tensiune nominala (III/2): 160; V Tensiune nominala de supratensiune (III/2): 2,5; kV Tensiune nominala (II/2): 320; V Tensiune nominala de supratensiune (II/2): 2,5; kV Curent nominal: 10; A Legend (ratings): (III / 2) %^o™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 10; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Tensiune nominala CSA (Use Group B): 300; V Curent nominal CSA (Use Group B): 10; A Tensiune nominala CSA (Use Group D): 300; V Curent nominal CSA (Use Group D): 10; A Tehnologie conexiune: Push-in CAGE CLAMP®; Tip actionare: Push-button; Solid conductor: 0.2 ... 1.5 mm² / 24 ... 16 AWG; Fine-stranded conductor: 0.2 ... 1.5 mm² / 24 ... 16 AWG; Fine-stranded conductor; with insulated ferrule: 0.25 ... 0.75 mm²; Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 1.5 mm²; Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch; Numar poli: 18; Numar total de conexiuni: 18; Total number of potentials: 18; Numar tipuri de conexiuni: 1; Numar nivele: 1; Conductor entry direction to mating direction: 0; ° Distanta intre pini: 3.5 mm / 0.138 inch; Latime: 77.8 mm / 3.063 inch; Inaltime: 14.7 mm / 0.579 inch; Adancime: 20.4 mm / 0.803 inch; Tip montaj: Mounting flange; Tip montaj: Feed-through mounting; Panel mounting; with reinforcing strips: 1; Tip contact (pluggable connector): Conector mama/priza; Connector (connection type): for conductors; Mismating protection: Yes; Culoare: light gray; Material group: I; Material izolator: Polyamide 66 (PA 66); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Copper alloy; Contact plating: tin-plated; Fire load: 0,328; MJ Greutate: 16,7; g Temperatura lucru: -60 ... +100 °C; Product Group: 3 (Multi Conn. System); Tip ambalare: BOX; Tara de origine: PL; GTIN: 4055143283045; Customs tariff number: 85366990990; Pret: 82,17 lei (TVA inclus) Detalii online: https://www.materialelectrice.ro/1-conductor-female-plug-100-protected-against-mismating-push-button-clamping-collar-1-5-mm2-pin-spacing-3-5-mm-18-pole-1-50-mm2-light-gray-135431
---	--