


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO 4-CONDUCTOR CHASSIS-MOUNT TERMINAL STRIP;  
SUITABLE FOR EX E II APPLICATIONS; 4-POLE; PE-N-L1-L2;  
WITHOUT GROUND CONTACT; 1 SNAP-IN FOOT PER POLE; 4 MM<sup>2</sup>;  
4,00 MM<sup>2</sup>; WHITE**

Tensiune nominala EN (Ex e II): 440; V  
Curent nominal (Ex e II): 28; A  
Tehnologie conexiune: Push-in CAGE CLAMP®;  
Tip actionare: Operating tool; Push-button;  
Connectable conductor materials: Copper;  
Solid conductor: 0.5 ... 4 mm<sup>2</sup> / 20 ... 12 AWG;  
Solid conductor; push-in termination: 0.75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;  
Stranded conductor: 0.5 ... 4 mm<sup>2</sup> / 20 ... 12 AWG;  
Fine-stranded conductor: 0.5 ... 4 mm<sup>2</sup> / 20 ... 12 AWG;  
Fine-stranded conductor; with insulated ferrule: 0.5 ... 2.5 mm<sup>2</sup> / 20 ... 12 AWG;  
Fine-stranded conductor; with ferrule; push-in termination: 0.75 mm<sup>2</sup> / 18 AWG;  
Strip length: 10 ... 11 mm / 0.39 ... 0.43 inch;  
Numar poli: 4;  
Numar total de conexiuni: 16;  
Total number of potentials: 4;  
Wiring type: Side-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;  
Distanta intre pini: 12 mm / 0.472 inch;  
Latime: 48 mm / 1.89 inch;  
Inaltime de la fata: 22.3 mm / 0.878 inch;  
Adancime: 35 mm / 1.378 inch;  
Tip montaj: Snap-in mounting foot;  
Marking: PE-N-L1-L2;  
Culoare: white;  
Fire load: 0,509; MJ  
Greutate: 27,4; g  
Tip ambalare: bag;  
Tara de origine: DE;  
GTIN: 4045454803599;  
Customs tariff number: 85369010000;  
Pret: 27,05 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/4-conductor-chassis-mount-terminal-strip-suitable-for-ex-e-ii-applications-4-pole-pe-n-l1-l2-without-ground-contact-1-snap-in-foot-per-pole-4-mm2-4-00-mm2-white-136206>