

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	WAGO PRE-ASSEMBLED ADAPTER CABLE; CCA; SOCKET/PLUG MIDI; 3-POLE; COD. S; 5 M; 1,50 MM²; BROWN Note on Contact Resistance: approx. 1 mΩ; of contact resistanceâ€© approx. 0.25 mΩ; contact transition plug/socket; Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 250; V Tensiune nominala de supratensiune (III/3): 4; kV Curent nominal: 16; A Legend (ratings): (III / 3) â‰‰™ Overvoltage category III / Pollution degree 3; Numar poli: 3; Conductor preparation: tip-bonded; Sheathed cable diameter: 7,4 ... 9,4 mm; Sectiunea transversala a firului: 1,5; mm² Connection type: RD socket - MIDI plug; Retention force of a plug-in connection: when locked: > 80N; Number of mating cycles: î»¿200, without resistive load100, with resistive load IN = 20 A, tested (2.5mm²/AWG 14); Connection type: RD socket - MIDI plug; Type of pre-assembled cable: Adapter cable; Cable type: H05Z1Z1-F 3x1.5; Protection type: IP20; Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).; Application: Switching function; Culoare: brown; Material izolator: Polyamide 66 (PA 66); Fire class per EN 50575: Cca; Contact material: Copper or copper alloy (surface-treated); Fire load: 0,164; MJ Processing temperature: -5 ... +40 °C; Continuous operating temperature: -35 ... +85 °C; Note on continuous operating temperature: PVC cable for temperatures ≤ 70 °C (including halogen-free) Insulating parts for temperatures ≤ 105 °C; Tip ambalare: not packed; Customs tariff number: 85444290900; Pret: 107,76 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/pre-assembled-adapter-cable-cca-socket-plug-midi-3-pole-cod-s-5-m-1-50-mm2-brown-137114
---	--