

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO PRE-ASSEMBLED ADAPTER CABLE; B2CA; SOCKET/PLUG
MIDI; 3-POLE; COD. S; 6 M; 1,50 MM²; BROWN**

Note on Contact Resistance: approx. 1 mΩ, of contact resistanceâ€© approx. 0.25 mΩ, contact transition plug/socket;
Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 250; V
Tensiune nominala de supratensiune (III/3): 4; kV
Curent nominal: 16; A
Legend (ratings): (III / 3) â‰‰™ Overvoltage category III / Pollution degree 3;
Numar poli: 3;
Conductor preparation: tip-bonded;
Sheathed cable diameter: 7,4 ... 9,4 mm;
Sectiunea transversala a firului: 1,5; mm²
Connection type: RD socket - MIDI plug;
Retention force of a plug-in connection: when locked: > 80N;
Number of mating cycles: î»¿200, without resistive load100, with resistive load IN = 20 A, tested (2.5mm²/AWG 14);
Connection type: RD socket - MIDI plug;
Type of pre-assembled cable: Adapter cable;
Cable type: H05Z1Z1-F 3x1.5;
Protection type: IP20;
Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;
Application: Switching function;
Culoare: brown;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: B2ca;
Contact material: Copper or copper alloy (surface-treated);
Fire load: 0,164; MJ
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ≤ 70 °C (including halogen-free) Insulating parts for temperatures ≤ 105 °C;
Tip ambalare: not packed;
Customs tariff number: 85444290900;
Pret: 135,34 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/pre-assembled-adapter-cable-b2ca-socket-plug-midi-3-pole-cod-s-6-m-1-50-mm2-brown-137127>