

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



WAGO PRE-ASSEMBLED CONNECTING CABLE; ECA; SOCKET/OPEN-ENDED; 5-POLE; COD. P: H05VV-F 5G 1.5 MMÂ²; 4M; 1.50 MMÂ²; RED

Note on Contact Resistance: approx. 1 mΩ, of contact resistance ≈ approx. 0.25 mΩ;
 contact transition plug/socket;
 Ratings per: IEC/EN 60664-1;
 Tensiune nominala (III/3): 400; V
 Tensiune nominala de supratensiune (III/3): 6; kV
 Current nominal: 16; A
 Legend (ratings): (III / 3) % Overvoltage category III / Pollution degree 3;
 Tensiune nominala UL 1977: 600; V
 Current nominal UL 1977: 23; A
 Strip length: 9 mm / 0.35 inch;
 Number of poles: 5;
 Total number of potentials: 5;
 Ground function: with preceding ground contact;
 Conductor preparation: tip-bonded;
 Sheathed cable diameter: 9,3 ... 11,6 mm;
 Cross-sectional area of the conductor: 1,5; mm²
 Strip length (outer insulation): 55; mm
 Connection type: Socket - Free end;
 Distance between pins: 10 mm / 0.394 inch;
 Total length: 4; m
 Coding: P;
 Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);
 Retention force of a plug-in connection: when locked: > 80N;
 Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);
 Number of mating cycles: 200 (without resistive load) 100 (with resistive load IN = 25 A), tested (4 mm²);
 Connection type: Socket - free end;
 Type of pre-assembled cable: Connecting cable;
 Cable type: H05VV-F 5G1.5;
 Marking: N L1 L2 L3;
 Protection type: IP20;
 Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas.);
 Potential marking: N L1 L2 L3;
 Application: Computer applications (UPS);
 Mismatching protection: Yes;
 Locking of plug-in connection: locking lever;
 Locking lever: retrofittable;
 Color: red;
 Material of insulation: Polyamide 66 (PA 66);
 Fire class per EN 50575: Eca;
 Contact material: Copper or copper alloy (surface-treated);
 Fire load: 11,58; MJ
 Connector Color: red;
 Printing color of mating face: white;
 Strain relief Color: black;
 Printing color of strain relief: white;
 Sheathed cable Color: black;
 Printing color of sheathed cable: white;
 Sheath material: PVC;
 Grease: 676,7; g
 Processing temperature: -5 ... +40 °C;
 Continuous operating temperature: -35 ... +85 °C;
 Note on continuous operating temperature: PVC cable for temperatures ≤ 70 °C (including halogen-free) Insulating parts for temperatures ≤ 105 °C;
 Tip assembly: not packed;
 GTIN: 4045454406646;
 Price: 0.00 lei (TVA included)

Detalii online: <https://www.materialeelectrice.ro/pre-assembled-connecting-cable-eca-socket-open-ended-5-pole-cod-p-h05vv-f-5g-1-5-mm2-4m-1-50-mm2-red-138372>