


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	WAGO THR MALE HEADER; 1.0 X 1.0 MM SOLDER PIN; ANGLED; PIN SPACING 7.5 MM; 12-POLE; BLACK Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 500; V Tensiune nominala de supratensiune (III/3): 6; kV Tensiune nominala (III/2): 630; V Tensiune nominala de supratensiune (III/2): 6; kV Tensiune nominala (II/2): 1000; V Tensiune nominala de supratensiune (II/2): 6; kV Curent nominal: 12; A Legend (ratings): (III / 2) %™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 10; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Tensiune nominala UL 1977: 600; V Curent nominal UL 1977: 10; A Tensiune nominala CSA (Use Group B): 300; V Curent nominal CSA (Use Group B): 10; A Tensiune nominala CSA (Use Group D): 300; V Curent nominal CSA (Use Group D): 10; A Numar poli: 12; Total number of potentials: 12; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 7.5 mm / 0.295 inch; Latime: 90.5 mm / 3.563 inch; Inaltime: 10.8 mm / 0.425 inch; Inaltime de la fata: 8.4 mm / 0.331 inch; Adancime: 12 mm / 0.472 inch; Lungimea pinului de contact: 2,4; mm Solder pin dimensions: 1 x 1 mm; Diametru placat prin gaura (THR): 1.4 (+0.1) mm; Tip contact (pluggable connector): Conector tata/fisa; Connector (connection type): for PCBs; Mismating protection: No; Mating direction to the PCB: 0; ° PCB contact: THR; Solder pin arrangement: over the entire male connector, in line; Number of solder pins per potential: 1; Culoare: black; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Contact material: Cupru electrolitic(ECu); Contact plating: tin-plated; Fire load: 0,113; MJ Greutate: 5,3; g Temperatura lucru: -60 ... +100 °C; Product Group: 3 (Multi Conn. System); Tip ambalare: BOX; Tara de origine: PL; GTIN: 4045454901233; Customs tariff number: 85366990990; Pret: 18,63 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/thr-male-header-1-0-x-1-0-mm-solder-pin-angled-pin-spacing-7-5-mm-12-pole-black-138429
--	--