

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>WAGO PRE-ASSEMBLED CONNECTING CABLE; SOCKET/OPEN-ENDED; 5-POLE; COD. A; H05Z1Z1-F 5G 4.0 MM²; 8 M; 4,00 MM²; BLACK</u> Note on Contact Resistance: approx. 1 mΩ; of contact resistanceâ€© approx. 0.25 mΩ; contact transition plug/socket; Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 400; V Tensiune nominala de supratensiune (III/3): 6; kV Curent nominal: 25; A Legend (ratings): (III / 3) â‰‰™ Overvoltage category III / Pollution degree 3; Tensiune nominala UL 1977: 600; V Curent nominal UL 1977: 23; A Strip length: 9 mm / 0.35 inch; Numar poli: 5; Total number of potentials: 5; Ground function: with preceding ground contact; Conductor preparation: tip-bonded; Sheathed cable diameter: 13 ... 16,1 mm; Sectiunea transversala a firului: 4; mm² Strip length (outer insulation): 55; mm Connection type: Socket - Free end; Distanta intre pini: 10 mm / 0.394 inch; Total length: 8; m Coding: A; Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number); Retention force of a plug-in connection: when locked: > 80N; Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number); Number of mating cycles: 200 (without resistive load) 100 (with resistive load IN = 25 A), tested (4 mm²); Connection type: Socket - free end; Type of pre-assembled cable: Connecting cable; Cable type: H05Z1Z1-F 5G4; Marking: N â‰š L1 L2 L3; Protection type: IP20; Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).; Potential marking: N â‰š L1 L2 L3; Application: General mains applications; Mismating protection: Yes; Locking of plug-in connection: locking lever; Locking lever: retrofittable; Culoare: black; Material izolator: Polyamide 66 (PA 66); Fire class per EN 50575: Eca; Contact material: Copper or copper alloy (surface-treated); Fire load: 0,801; MJ Connector Culoare: black; Printing color of mating face: white; Strain relief Culoare: black; Printing color of strain relief: white; Sheathed cable Culoare: black; Printing color of sheathed cable: white; Halogen-free: Yes; Greutate: 2919,5; g Processing temperature: -5 ... +40 °C; Continuous operating temperature: -35 ... +85 °C; Note on continuous operating temperature: PVC cable for temperatures ≤ 70 °C (including halogen-free) Insulating parts for temperatures ≤ 105 °C; Tip ambalare: not packed; Tara de origine: DE; GTIN: 4055143521512; Customs tariff number: 85444290900; Pret: 295,37 lei (TVA inclus) Detalii online: https://www.materialelectrice.ro/pre-assembled-connecting-cable-socket-open-ended-5-pole-cod-a-h05z1z1-f-5g-4-0-mm2-8-m-4-00-mm2-black-139367
---	---