


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

 Technical drawing of the WAGO THT Female Header showing three views: top, side, and front. Dimensions are provided in millimeters: top view shows a width of 33.4 mm, a pitch of 7.5 mm, and a height of 12.5 mm; side view shows a height of 16.2 mm and a width of 15.7 mm; front view shows a height of 4.6 mm and a width of 2.5 mm.	<u>WAGO THT FEMALE HEADER; 0.4 X 1.3 MM SOLDER PIN; ANGLED; PIN SPACING 7.5 MM; 5-POLE; LIGHT GRAY</u> Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 400; V Tensiune nominala de supratensiune (III/3): 6; kV Tensiune nominala (III/2): 630; V Tensiune nominala de supratensiune (III/2): 6; kV Tensiune nominala (II/2): 1000; V Tensiune nominala de supratensiune (II/2): 6; kV Curent nominal: 16; A Legend (ratings): (III / 2) %™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 15; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Numar poli: 5; Total number of potentials: 5; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 7,5 mm / 0.295 inch; Latime: 35 mm / 1.378 inch; Inaltime: 17,2 mm / 0.677 inch; Inaltime de la fata: 13,6 mm / 0.535 inch; Adancime: 15,4 mm / 0.606 inch; Lungimea pinului de contact: 3,6; mm Solder pin dimensions: 0,4 x 1,3 mm; Diametrul de gaurire cu toleranta: 1,5 (+0,1) mm; Tip contact (pluggable connector): Conector mama/priza; Connector (connection type): for PCB; Mismatching protection: No; Mating direction to the PCB: 0; ° PCB contact: THT; Culoare: light gray; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Contact material: Copper alloy; Contact plating: tin-plated; Fire load: 0,156; MJ Greutate: 6,2; g Temperatura lucru: -60 ... +100 °C; Product Group: 26 (picoMAX); Tip ambalare: BOX; Tara de origine: DE; GTIN: 4050821164548; Customs tariff number: 85366990990; Pret: 19,64 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/tht-female-header-0-4-x-1-3-mm-solder-pin-angled-pin-spacing-7-5-mm-5-pole-light-gray-139706
---	--