

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>WAGO PRE-ASSEMBLED CONNECTING CABLE; ECA; SOCKET/OPEN-ENDED; 2-POLE; COD. A; H05VV-F 2 X 2.5 MM²; 7 M; 2.50 MM²; WHITE</u> Note on Contact Resistance: approx. 1 mΩ; of contact resistanceâ€© approx. 0.25 mΩ; contact transition plug/socket; Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 250; V Tensiune nominala de supratensiune (III/3): 4; kV Curent nominal: 20; A Legend (ratings): (III / 3) â‰‰™ Overvoltage category III / Pollution degree 3; Tensiune nominala UL 1977: 600; V Curent nominal UL 1977: 23; A Numar poli: 2; Total number of potentials: 2; Conductor preparation: tip-bonded; Sheathed cable diameter: 8,4 ... 10,6 mm; Sectiunea transversala a firului: 2,5; mm² Strip length (outer insulation): 35; mm Connection type: Socket - Free end; Distanta intre pini: 10 mm / 0.394 inch; Total length: 7; m Coding: A; Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number); Retention force of a plug-in connection: when locked: > 80N; Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number); Number of mating cycles: 200 (without resistive load) 100 (with resistive load IN = 25 A), tested (4 mm²); Connection type: Socket - Free end; Type of pre-assembled cable: Connecting cable; Cable type: H05VV-F 2x2.5; Marking: L N; Protection type: IP20; Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).; Potential marking: L N; Application: General mains applications; Mismating protection: Yes; Locking of plug-in connection: locking lever; Locking lever: retrofittable; Culoare: white; Material izolator: Polyamide 66 (PA 66); Fire class per EN 50575: Eca; Contact material: Copper or copper alloy (surface-treated); Fire load: 0,306; MJ Connector Culoare: white; Printing color of mating face: black; Strain relief Culoare: white; Printing color of strain relief: black; Sheathed cable Culoare: white; Printing color of sheathed cable: black; Sheath material: PVC; Greutate: 900; g Processing temperature: -5 ... +40 °C; Continuous operating temperature: -35 ... +85 °C; Note on continuous operating temperature: PVC cable for temperatures ≤ 70 °C (including halogen-free) Insulating parts for temperatures ≤ 105 °C; Tip ambalare: not packed; Tara de origine: DE; GTIN: 4055143525848; Customs tariff number: 85444290900; Pret: 67,23 lei (TVA inclus) Detalii online: https://www.materialelectrice.ro/pre-assembled-connecting-cable-eca-socket-open-ended-2-pole-cod-a-h05vv-f-2-x-2-5-mm2-7-m-2-50-mm2-white-139711
---	---