

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO 4-CONDUCTOR CHASSIS-MOUNT TERMINAL STRIP;
SUITABLE FOR EX E II APPLICATIONS; 5-POLE; PE-N-L1-L2-L3;
WITHOUT GROUND CONTACT; FOR 3 MM $\tilde{A}$ SCREW AND NUT; 4
MM $\tilde{A}$ 2; 4,00 MM $\tilde{A}$ 2; BLACK**

Tensiune nominala EN (Ex e II): 440; V
Curent nominal (Ex e II): 28; A
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Operating tool; Push-button;
Connectable conductor materials: Copper;
Solid conductor: 0.5 ... 4 mm $\tilde{A}$ 2 / 20 ... 12 AWG;
Solid conductor; push-in termination: 0.75 ... 4 mm $\tilde{A}$ 2 / 18 ... 12 AWG;
Stranded conductor: 0.5 ... 4 mm $\tilde{A}$ 2 / 20 ... 12 AWG;
Fine-stranded conductor: 0.5 ... 4 mm $\tilde{A}$ 2 / 20 ... 12 AWG;
Fine-stranded conductor; with insulated ferrule: 0.5 ... 2.5 mm $\tilde{A}$ 2 / 20 ... 12 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 0.75 mm $\tilde{A}$ 2 / 18 AWG;
Strip length: 10 ... 11 mm / 0.39 ... 0.43 inch;
Numar poli: 5;
Numar total de conexiuni: 20;
Total number of potentials: 5;
Wiring type: Side-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;
Distanta intre pini: 12 mm / 0.472 inch;
Latime: 60 mm / 2.362 inch;
Inaltime de la fata: 22.3 mm / 0.878 inch;
Adancime: 35 mm / 1.378 inch;
Tip montaj: Screw mounting;
Marking: PE-N-L1-L2-L3;
Culoare: black;
Fire load: 0,641; MJ
Greutate: 34,1; g
Tip ambalare: bag;
Tara de origine: DE;
GTIN: 4045454789213;
Customs tariff number: 85369010000;
Pret: 31,47 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/4-conductor-chassis-mount-terminal-strip-suitable-for-ex-e-ii-applications-5-pole-pe-n-l1-l2-l3-without-ground-contact-for-3-mm-oe-screw-and-nut-4-mm2-4-00-mm2-black-140606>