

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO 3-CONDUCTOR THROUGH TERMINAL BLOCK; 2.5 MM²;
SUITABLE FOR EX I APPLICATIONS; CENTER MARKING; FOR DIN-
RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 2,50 MM²; BLUE**

Ratings per: IEC/EN 60947-7-1;
Tensiune nominala (III/3): 800; V
Tensiune nominala de supratensiune (III/3): 8; kV
Curent nominal: 24; A
Legend (ratings): (III / 3) %™ Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper; Aluminum;
Solid conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;
Fine-stranded conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;
Numar total de conexiuni: 3;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Note (conductor cross-section): 12 AWG: THHN, THWN;
Latime: 5 mm / 0.197 inch;
Inaltime from upper-edge of DIN-rail: 36,5 mm / 1.437 inch;
Adancime: 50,5 mm / 1.988 inch;
Design: angled;
Tip montaj: DIN-35 rail;
Marking level: Center marking;
Culoare: blue;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,121; MJ
Greutate: 6,7; g
Product Group: 1 (Rail Mounted Terminal Blocks);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918325912;
Customs tariff number: 85369010000;
Pret: 7,70 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/3-conductor-through-terminal-block-2-5-mm2-suitable-for-ex-i-applications-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-2-50-mm2-blue-140853>