


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>WAGO 1-CONDUCTOR MALE CONNECTOR; CLAMPING COLLAR; 2.5 MM²; PIN SPACING 5 MM; 12-POLE; 2,50 MM²; GRAY</u> Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 320; V Tensiune nominala de supratensiune (III/3): 4; kV Tensiune nominala (III/2): 320; V Tensiune nominala de supratensiune (III/2): 4; kV Tensiune nominala (II/2): 630; V Tensiune nominala de supratensiune (II/2): 4; kV Curent nominal: 12; A Legend (ratings): (III / 2) %TM Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 15; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Tensiune nominala UL 1977: 600; V Curent nominal UL 1977: 15; A Tensiune nominala CSA (Use Group B): 300; V Curent nominal CSA (Use Group B): 15; A Tensiune nominala CSA (Use Group D): 300; V Curent nominal CSA (Use Group D): 10; A Tehnologie conexiune: CAGE CLAMP®; Tip actionare: Operating tool; Solid conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG; Fine-stranded conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG; Fine-stranded conductor; with insulated ferrule: 0,25 ... 1,5 mm²; Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 2,5 mm²; Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch; Numar poli: 12; Numar total de conexiuni: 12; Total number of potentials: 12; Numar tipuri de conexiuni: 1; Numar nivele: 1; Conductor entry direction to mating direction: 0; ° Distanta intre pini: 5 mm / 0.197 inch; Latime: 74,8 mm / 2.945 inch; Inaltime: 14,3 mm / 0.563 inch; Adancime: 27,5 mm / 1.083 inch; Tip montaj: Mounting flange; Tip montaj: Feed-through mounting; Panel mounting; Tip contact (pluggable connector): Conector tata/fisa; Connector (connection type): for conductor; Mismating protection: No; Culoare: gray; Material group: I; Material izolator: Polyamide 66 (PA 66); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Cupru electrolitic (ECu); Contact plating: tin-plated; Fire load: 0,343; MJ Greutate: 19,3; g Temperatura lucru: -60 ... +100 °C; Product Group: 3 (Multi Conn. System); Tip ambalare: BOX; Tara de origine: DE; GTIN: 4044918258401; Customs tariff number: 85366990990; Pret: 41,67 lei (TVA inclus) Detalii online: https://www.materialelectrice.ro/1-conductor-male-connector-clamping-collar-2-5-mm2-pin-spacing-5-mm-12-pole-2-50-mm2-gray-141066
---	---