


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO TRIPLE-DECK TERMINAL BLOCK;
THROUGH/THROUGH/THROUGH TERMINAL BLOCK; L/L/N; WITH
MARKER CARRIER; SUITABLE FOR EX E II APPLICATIONS; BLUE
CONDUCTOR ENTRY UPPER DECK; FOR DIN-RAIL 35 X 15 AND 35 X
7.5; 2.5 MM²; PUSH-IN CAGE CLAMP®; 2.50 MM²; GRAY**

Ratings per: IEC/EN 60947-7-1;
Tensiune nominala (III/3): 500; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 24; A
Curent nominal 2: 28; A
Legend (ratings): (III / 3) %™ Overvoltage category III / Pollution degree 3;
Tensiune nominala UL (Use Group B): 300; V
Curent nominal UL (Use Group B): 20; A
Tensiune nominala UL (Use Group C): 300; V
Curent nominal UL (Use Group C): 20; A
Tensiune nominala UL (Use Group D): 600; V
Curent nominal UL (Use Group D): 5; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group B): 600; V
Curent nominal CSA (Use Group B): 20; A
Tensiune nominala CSA (Use Group C): 600; V
Curent nominal CSA (Use Group C): 20; A
Tensiune nominala EN (Ex e II): 440; V
Curent nominal (Ex e II): 19; A
Curent nominal (Ex e II) with jumper: 17; A
Tehnologie conexiune: Push-in CAGE CLAMP®;
Number of connection points (connection type): 3;
Tip actionare: Push-in; Open Tool Slot;
Connectable conductor materials: Copper;
Nominal cross-section: 2,5 mm²;
Solid conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;
Solid conductor; push-in termination: 0,75 ... 4 mm² / 18 ... 12 AWG;
Fine-stranded conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;
Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm² / 18 ... 12 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm² / 18 ... 12 AWG;
Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;
Number of connection points: 3;
Numar total de conexiuni: 6;
Total number of potentials: 3;
Numar nivele: 3;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination;
Latime: 5,2 mm / 0.205 inch;
Inaltime from upper-edge of DIN-rail: 81,3 mm / 3.201 inch;
Adancime: 93,3 mm / 3.673 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Potential marking: L/L/N;
Marking level: Center/side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,336; MJ
Greutate: 17,5; g
Product Group: 22 (TOPJOB S);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918989749;
Customs tariff number: 85369010000;
Pret: 21,20 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/triple-deck-terminal-block-through-through-through-terminal-block-l-l-n-with-marker-carrier-suitable-for-ex-e-ii-applications-blue-conductor-entry-upper-deck-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-gray-143505>