


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	WAGO DOUBLE-DECK TERMINAL BLOCK; THROUGH/THROUGH TERMINAL BLOCK; N/L; WITH MARKER CARRIER; SUITABLE FOR EX E II APPLICATIONS; BLUE CONDUCTOR ENTRY LOWER DECK; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM²; PUSH-IN CAGE CLAMP®; 2.50 MM²; GRAY Ratings per: IEC/EN 60947-7-1; Tensiune nominala (III/3): 500; V Tensiune nominala de supratensiune (III/3): 6; kV Curent nominal: 24; A Curent nominal 2: 28; A Legend (ratings): (III / 3) %™ Overvoltage category III / Pollution degree 3; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 20; A Tensiune nominala UL (Use Group C): 300; V Curent nominal UL (Use Group C): 20; A Tensiune nominala UL (Use Group D): 600; V Curent nominal UL (Use Group D): 5; A Certificari: UL 1059; Tensiune nominala CSA (Use Group B): 600; V Curent nominal CSA (Use Group B): 20; A Tensiune nominala CSA (Use Group C): 600; V Curent nominal CSA (Use Group C): 20; A Tensiune nominala EN (Ex e II): 440; V Curent nominal (Ex e II): 20; A Curent nominal (Ex e II) with jumper: 18; A Tehnologie conexiune: Push-in CAGE CLAMP®; Number of connection points (connection type): 2; Tip actionare: Push-in; Open Tool Slot; Connectable conductor materials: Copper; Nominal cross-section: 2,5 mm²; Solid conductor: 0,25 ... 4 mm² / 22 ... 12 AWG; Solid conductor; push-in termination: 0,75 ... 4 mm² / 18 ... 12 AWG; Fine-stranded conductor: 0,25 ... 4 mm² / 22 ... 12 AWG; Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm² / 18 ... 12 AWG; Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm² / 18 ... 12 AWG; Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch; Number of connection points: 2; Numar total de conexiuni: 4; Total number of potentials: 2; Numar nivele: 2; Wiring type: Front-entry wiring; Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination; Latime: 5,2 mm / 0.205 inch; Inaltime from upper-edge of DIN-rail: 61,8 mm / 2.433 inch; Adancime: 69,7 mm / 2.744 inch; Design: horizontal; Tip montaj: DIN-35 rail; Potential marking: N/L; Marking level: Center/side marking; Culoare: gray; Material izolator: Polyamide 66 (PA 66); Fire load: 0,218; MJ Greutate: 10,6; g Product Group: 22 (TOPJOB S); Tip ambalare: BOX; Tara de origine: DE; GTIN: 4044918964791; Customs tariff number: 85369010000; Pret: 12,90 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/double-deck-terminal-block-through-through-terminal-block-n-l-with-marker-carrier-suitable-for-ex-e-ii-applications-blue-conductor-entry-lower-deck-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-gray-143606
---	--