

	WAGO 1-CONDUCTOR FEMALE PLUG; CLAMPING COLLAR; 2.5 MM²; PIN SPACING 5.08 MM; 6-POLE; 2,50 MM²; ORANGE Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 320; V Tensiune nominala de supratensiune (III/3): 4; kV Tensiune nominala (III/2): 320; V Tensiune nominala de supratensiune (III/2): 4; kV Tensiune nominala (II/2): 630; V Tensiune nominala de supratensiune (II/2): 4; kV Curent nominal: 16; A Legend (ratings): (III / 2) $\hat{a}\%$™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 15; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Tensiune nominala UL 1977: 600; V Curent nominal UL 1977: 15; A Tensiune nominala CSA (Use Group B): 300; V Curent nominal CSA (Use Group B): 15; A Tensiune nominala CSA (Use Group D): 300; V Curent nominal CSA (Use Group D): 10; A Tehnologie conexiune: CAGE CLAMP®; Tip actionare: Operating tool; Solid conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG; Fine-stranded conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG; Fine-stranded conductor; with insulated ferrule: 0,25 ... 1,5 mm²; Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 2,5 mm²; Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch; Numar poli: 6; Numar total de conexiuni: 6; Total number of potentials: 6; Numar tipuri de conexiuni: 1; Numar nivele: 1; Conductor entry direction to mating direction: 0; ° Distanta intre pini: 5,08 mm / 0.2 inch; Latime: 45,28 mm / 1.783 inch; Inaltime: 14,3 mm / 0.563 inch; Adancime: 26,45 mm / 1.041 inch; Tip montaj: Mounting flange; Tip montaj: Feed-through mounting; Panel mounting; with reinforcing strips: 1; Tip contact (pluggable connector): Conector mama/priza; Connector (connection type): for conductors; Mismating protection: No; Culoare: orange; Material group: I; Material izolator: Polyamide 66 (PA 66); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Copper alloy; Contact plating: tin-plated; Fire load: 0,184; MJ Greutate: 12; g Temperatura lucru: -60 ... +85 °C; Product Group: 3 (Multi Conn. System); Tip ambalare: BOX; Tara de origine: DE; GTIN: 4044918346887; Customs tariff number: 85366990990; Pret: 30,45 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/1-conductor-female-plug-clamping-collar-2-5-mm2-pin-spacing-5-08-mm-6-pole-2-50-mm2-orange-143746
---	---