

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO 2-CONDUCTOR FUSE TERMINAL BLOCK; FOR CYLINDRICAL
FUSES 10 X 38 MM; 13/32" X 11/2"; 3-POLE; WITHOUT BLOWN FUSE
INDICATION; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 16 MMÂ²; CAGE
CLAMPÂ®; 16,00 MMÂ²; LIGHT GRAY**

Voltage type 1: AC;
Voltage type 2: DC;
Ratings per: IEC/EN 60947-7-3;
Tesiune nominala (III/3): 690; V
Curent nominal: 32; A
Tensiune nominala (III/3) 2: 1000; V
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Solid conductor: 2,5 ... 16 mm² / 14 ... 6 AWG;
Fine-stranded conductor: 2,5 ... 16 mm² / 16 ... 6 AWG;
Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;
Numar poli: 3;
Numar total de conexiuni: 6;
Total number of potentials: 3;
Numar nivele: 1;
Wiring type: Side-entry wiring;
Latime: 52,5 mm / 2.067 inch;
Inaltime from upper-edge of DIN-rail: 55 mm / 2.165 inch;
Adancime: 105 mm / 4.134 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Culoare: light gray;
Material izolator: Polyamide 66 (PA 66);
Greutate: 200; g
Product Group: 1 (Rail Mounted Terminal Blocks);
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4050821877660;
Customs tariff number: 85369095990;
Pret: 224,81 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-fuse-terminal-block-for-cylindrical-fuses-10-x-38-mm-13-32-x-11-2-3-pole-without-blown-fuse-indication-for-din-rail-35-x-15-and-35-x-7-5-16-mm2-cage-clamp-16-00-mm2-light-gray-144251>