

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO SHORTING PLUG; WITH ASSEMBLED STRAIN RELIEF
HOUSING; 3-POLE; COD. A; BRIDGE L-N; 4.00 MM²; BLACK**

Tensiune nominala (III/3): 250; V
Tensiune nominala de supratensiune (III/3): 4; kV
Curent nominal: 25; A
Legend (ratings): (III / 3) $\hat{a}\%$ ™ Overvoltage category III / Pollution degree 3;
Tensiune nominala UL 1977: 600; V
Curent nominal UL 1977: 23; A
Tehnologie conexiune: Push-in CAGE CLAMP®;
Note (strip length): see also packaging or instructions;
Numar poli: 3;
Distanța între pini: 10 mm / 0.394 inch;
Latime: 34,6 mm / 1.362 inch;
Inaltime: 15 mm / 0.591 inch;
Adancime: 76 mm / 2.992 inch;
Coding: A;
Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);
Retention force of a plug-in connection: when locked: > 80N;
Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);
Marking: $\hat{a}$ "CE $\hat{a}$ " $\hat{e}$ $\hat{a}$ " $\hat{e}$ $\hat{a}$ " $\hat{e}$ $\hat{a}$ ";
Protection type: IP20;
Note on protection type: In mated condition with strain relief housing: IP2xC (These compact connectors are not designed for use in open, easily accessible areas.);
Application: Standard network application;
Suitable: for distribution connector; series and two-way circuits;
Tip contact (pluggable connector): Conector tata/fisa;
Connector (connection type): for pluggable connectors;
Locking lever: no;
Strain relief: strain relief housing;
Culoare: black;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Copper or copper alloy; surface-treated;
Fire load: 0,476; MJ
Connector Culoare: black;
Greutate: 23,5; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: Insulating parts for temperatures $\leq$ 105 °C;
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454729455;
Customs tariff number: 85366990990;
Pret: 26,93 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/shorting-plug-with-assembled-strain-relief-housing-3-pole-cod-a-bridge-l-n-4-00-mm2-black-145918>