


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>WAGO BOARD-TO-BOARD LINK; PIN SPACING 3 MM; 3-POLE; LENGTH: 15.3 MM; WHITE</u> Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 63; V Tensiune nominala de supratensiune (III/3): 2,5; kV Tensiune nominala (III/2): 160; V Tensiune nominala de supratensiune (III/2): 2,5; kV Tensiune nominala (II/2): 320; V Tensiune nominala de supratensiune (II/2): 2,5; kV Curent nominal: 3; A Legend (ratings): (III / 2) % Overvoltage category III / Pollution degree 2; Certificari: UL 1059; Numar poli: 3; Total number of potentials: 3; Numar tipuri de conexiuni: 1; Distanta intre pini: 3 mm / 0.118 inch; Latime: 8,7 mm / 0.343 inch; Inaltime: 2,5 mm / 0.098 inch; Adancime: 15,3 mm / 0.602 inch; Mating cycles (max.): 10; Number of mating cycles: max. 10 connections/disconnections; Suitable: for SMD PCB Terminal Blocks; 2059 Series; Culoare: white; Material group: I; Material izolator: Polyamide 66 (PA 66); Flammability class per UL94: V0; Contact material: Copper alloy; Contact plating: silver-plated; Greutate: 0,2; g Temperatura lucru: -60 ... +105 °C; Tip ambalare: BOX; Tara de origine: CN; GTIN: 4055143610063; Customs tariff number: 85369010000; Pret: 3,46 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/board-to-board-link-pin-spacing-3-mm-3-pole-length-15-3-mm-white-147705
---	---