


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO SHORTING PLUG; WITH ASSEMBLED STRAIN RELIEF HOUSING; 3-POLE; COD. S; BRIDGE 2-L; 4,00 MM<sup>2</sup>; BROWN**

Tensiune nominala (III/3): 250; V  
Tensiune nominala de supratensiune (III/3): 4; kV  
Curent nominal: 25; A  
Legend (ratings): (III / 3)  $\hat{a}\%$ ™ Overvoltage category III / Pollution degree 3;  
Tensiune nominala UL 1977: 600; V  
Curent nominal UL 1977: 23; A  
Tehnologie conexiune: Push-in CAGE CLAMP®;  
Note (strip length): see also packaging or instructions;  
Numar poli: 3;  
Distanța între pini: 10 mm / 0.394 inch;  
Latime: 34,6 mm / 1.362 inch;  
Inaltime: 15 mm / 0.591 inch;  
Adancime: 76 mm / 2.992 inch;  
Coding: S;  
Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);  
Retention force of a plug-in connection: when locked: > 80N;  
Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);  
Marking:  $\hat{a}$ "CE $\hat{a}$ " $\hat{a}$ ";  
Protection type: IP20;  
Note on protection type: In mated condition with strain relief housing: IP2xC (These compact connectors are not designed for use in open, easily accessible areas.);  
Application: Switch function;  
Suitable: for distribution connector; series and two-way circuits;  
Tip contact (pluggable connector): Conector tata/fisa;  
Connector (connection type): for pluggable connectors;  
Locking lever: no;  
Strain relief: strain relief housing;  
Culoare: brown;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Copper or copper alloy; surface-treated;  
Fire load: 0,472; MJ  
Connector Culoare: brown;  
Greutate: 23,2; g  
Processing temperature: -5 ... +40 °C;  
Continuous operating temperature: -35 ... +85 °C;  
Note on continuous operating temperature: Insulating parts for temperatures  $\leq$  105 °C;  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4045454148317;  
Customs tariff number: 85366990990;  
Pret: 28,48 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/shorting-plug-with-assembled-strain-relief-housing-3-pole-cod-s-bridge-2-l-4-00-mm2-brown-149312>