

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul sens
giratoriu Tehodor Pallady-Autostrada
Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



WAGO POWER SUPPLY CONNECTOR

Tensiune nominala (III/2): 400; V
Tensiune nominala de supratensiune (III/2): 4; kV
Curent nominal: 18; A
Legend (ratings): (III / 2) â‰‰™ Overvoltage category III / Pollution degree 2;
Certificari: UL 1059;
Tehnologie conexiune: PUSH WIRE®;
Solid conductor: 0,5 ... 1,5 mm² / 20 ... 16 AWG;
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;
Numar poli: 1;
Solid conductor 2: 0,5 ... 2,5 mm² / 20 ... 14 AWG;
Numar total de conexiuni: 4;
Total number of potentials: 1;
Numar tipuri de conexiuni: 1;
Latime: 8,5 mm / 0.335 inch;
Inaltime: 19 mm / 0.748 inch;
Adancime: 24,5 mm / 0.965 inch;
Fire load: 0,113; MJ
Greutate: 3,1; g
Tip ambalare: bag;
Tara de origine: DE;
GTIN: 4044918439497;
Customs tariff number: 85369010000;
Pret: 3,16 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/power-supply-connector-150809>