

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO H-DISTRIBUTION CONNECTOR; 3-POLE; COD. A; 1 INPUT; 2
OUTPUTS; OUTPUTS ON ONE SIDE; 2 LOCKING LEVERS; WHITE**

Note on Contact Resistance: approx. 1 mΩ; of contact resistance ≈ approx. 0.25 mΩ; contact transition plug/socket;
Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 250; V
Tensiune nominala de supratensiune (III/3): 4; kV
Curent nominal: 16; A
Legend (ratings): (III / 3) % Overvoltage category III / Pollution degree 3;
Tensiune nominala UL 1977: 600; V
Curent nominal UL 1977: 14; A
Numar poli: 3;
Total number of potentials: 3;
Ground function: with preceding ground contact;
Distanta intre pini: 4,4 mm / 0.173 inch;
Latime: 16,4 mm / 0.646 inch;
Inaltime: 29 mm / 1.142 inch;
Adancime: 57,85 mm / 2.278 inch;
Coding: A;
Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);
Retention force of a plug-in connection: When locked: > 80 N;
Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);
Number of mating cycles: ≥200, without resistive load 100, with resistive load IN = 16 A, tested (1.5mm²/AWG 16);
Distributor type: h-distribution connector (unidirectional);
Marking: L & N;
Protection type: IP20;
Note on protection type: IP40 when mated;
Potential marking: L & N;
Application: General mains applications;
Tip contact (pluggable connector): Socket/plug;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: yes;
Culoare: white;
Material izolator: Polyamide 66 (PA 66);
Contact material: Copper or copper alloy (surface-treated);
Fire load: 0,237; MJ
Greutate: 13,4; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: Insulating parts for temperatures ≤ 105 °C;
Product Group: 20 (WINSTA);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454404451;
Customs tariff number: 85366990990;
Pret: 32,12 lei (TVA inclus)

Detalii online: <https://www.materialeelectric.ro/h-distribution-connector-3-pole-cod-a-1-input-2-outputs-outputs-on-one-side-2-locking-levers-white-150907>