


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<u>WAGO DISTRIBUTION CONNECTOR FOR SWITCHES; SINGLE-POLE SWITCH AND SERIES CIRCUIT; 3-POLE; COD. A/S; 1 INPUT; 5 OUTPUTS; WHITE</u> Note on Contact Resistance: approx. 1 mΩ; of contact resistanceâ€© approx. 0.25 mΩ; contact transition plug/socket; Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 250; V Tensiune nominala de supratensiune (III/3): 4; kV Curent nominal: 25; A Legend (ratings): (III / 3) â‰‰™ Overvoltage category III / Pollution degree 3; Tensiune nominala UL 1977: 600; V Curent nominal UL 1977: 23; A Numar poli: 3; Total number of potentials: 3; Distanta intre pini: 10 mm / 0.394 inch; Latime: 38 mm / 1.496 inch; Inaltime: 52,5 mm / 2.067 inch; Adancime: 46 mm / 1.811 inch; Coding: A; Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number); Retention force of a plug-in connection: When locked: > 80 N; Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number); Number of mating cycles: î»¿200, without resistive load 100, with resistive load IN = 25 A, tested (4 mm²/AWG 12); Distributor type: Distribution connector for single-pole switch or series circuits; Protection type: IP20; Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).; Application: General mains applications; Suitable: for single-pole switch and series circuits; Tip contact (pluggable connector): Socket/plug; Mismating protection: Yes; Locking of plug-in connection: locking lever; Locking lever: yes; Culoare: white; Material izolator: Polyamide 66 (PA 66); Contact material: Copper or copper alloy (surface-treated); Fire load: 0,695; MJ Greutate: 44,3; g Processing temperature: -5 ... +40 °C; Continuous operating temperature: -35 ... +85 °C; Note on continuous operating temperature: Insulating parts for temperatures ≤ 105 °C; Tip ambalare: BOX; Tara de origine: DE; GTIN: 4045454251598; Customs tariff number: 85366990990; Pret: 80,26 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/distribution-connector-for-switches-single-pole-switch-and-series-circuit-3-pole-cod-a-s-1-input-5-outputs-white-151191
---	---