

	WAGO 1-CONDUCTOR MALE CONNECTOR; GRIPPING PLATE; 2.5 MM²; PIN SPACING 7.5 MM; 3-POLE; 2,50 MM²; LIGHT GRAY Ratings per: IEC/EN 60664-1; Tensiune nominală (III/3): 400; V Tensiune nominală de supratensiune (III/3): 6; kV Tensiune nominală (III/2): 630; V Tensiune nominală de supratensiune (III/2): 6; kV Tensiune nominală (II/2): 1000; V Tensiune nominală de supratensiune (II/2): 6; kV Curent nominal: 16; A Legend (ratings): (III / 2) % Overvoltage category III / Pollution degree 2; Tensiune nominală UL (Use Group B): 300; V Curent nominal UL (Use Group B): 15; A Tensiune nominală UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Tehnologie conexiune: Push-in CAGE CLAMP®; Tip actionare: Push-button; Solid conductor: 0.2 ... 2.5 mm² / 24 ... 12 AWG; Fine-stranded conductor: 0.2 ... 2.5 mm² / 24 ... 12 AWG; Fine-stranded conductor; with insulated ferrule: 0.25 ... 1.5 mm²; Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 2.5 mm²; Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch; Numar poli: 3; Numar total de conexiuni: 3; Total number of potentials: 3; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanța între pini: 7.5 mm / 0.295 inch; Latime: 22.2 mm / 0.874 inch; Inaltime: 18.2 mm / 0.717 inch; Adancime: 51.8 mm / 2.039 inch; Design: With gripping plate; Tip contact (pluggable connector): Conector tata/fisa; Connector (connection type): for conductors; Mismatching protection: No; Locking of plug-in connection: Male locking latch; Culoare: light gray; Material group: I; Material izlator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Cupru electrolitic(ETCu); Contact plating: tin-plated; Fire load: 0,201; MJ Greutate: 8,2; g Temperatura lucru: -60 ... +100 °C; Product Group: 26 (picoMAX); Tip ambalare: BOX; Tara de origine: DE; GTIN: 4050821164807; Customs tariff number: 85366990990; Pret: 16,24 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/1-conductor-male-connector-gripping-plate-2-5-mm2-pin-spacing-7-5-mm-3-pole-2-50-mm2-light-gray-152015
--	--