

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



GEWISS LAMPA STRADALA ROAD [5] - MEDIUM - 3 (3X3 LED) - DALI
- WIDE OPTIC - 3000 K - 0.5A - IP66 - CLASS II

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Street and parking lighting
Optic - WIDE
Luminaire - LED Road Equipment
Unified Glare Rating - G*3 - ULOR = 0
Aplicatie - Exterior
Luminanta (lm) - 6100
Unique digital code (Datamatrix) - Currently not present
Efficiency
(lm/W) - 105
Culoare - Gri grafit
Culoare Temperatur - 3000 K
Tip sursă de lumină - LED - Neînlocuibil
Color Rendering Index - CRI>70
System
power - 58 W @ 0.5A
Standard Deviation Colour Matching - SDCM = 5
LED Lifetime - L90B10(Tq25°C)>115.000h; L90B10(Tq50°C)=115.000h
Photobiological Risk Class - RG0
Greutate (Kg) - 8
Standard - EN 60598-2-3, EN 60598-1 IEC/TR 62778
Garanție - 5 ani
ELECTRICAL AND LIGHTING FEATURES - -
Temperatură de stocare - -
Tensiune de alimentare - 220 - 240 V
Operating temperature - -25 +50 °C
Frecvență nominală (Hz) - 50 / 60
MATERIALS - -
Driver failure rate - F10=100.000h Tq25°C/75.000h Tq50°C
Body - Aluminiu turnat
Driver - Included
Ecran - 4mm thick flat tempered glass
Overvoltage protection - DM 10KV / CM 10KV
Optic - Metallized polycarbonate reflector
Control System - DALI
Gasket - Anti-aging silicone
INSTALLATION AND MAINTENANCE - -
Locking Hook - Integrated front handle
Mounting and installation - Pole Head - Outreach
External screw - Oțel
Tilt - Console cu acces pe lateral -20° ÷ +10° - -10° ÷ +20° cap de stalp
Colour - Powder coating
Wiring - Intrerupător secționator
STANDARDS AND APPROVALS - -
Prindere - Pole Head - Outreach
Clasificare - -
Optic Maintenance - Not available
Dispozitiv cu temperatură la suprafață redusă - -
LED Maintenance - Not available
Certificare DIN 18032-3 - -
Driver Box - Integrat
IPEA - -
Suprafață maximă expusă la vant - 0.19 m²
Clasă izolație - II
- - -
Clasă de protecție IP - IP66
- - -
Cod IK - IK08
- - -
Glow Test conductori - -
- - -
Ware number -
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/lampa-stradala-road-5-medium-3-3x3-led-dali-wide-optic-3000-k-0-5a-ip66-class-ii-215897>