

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

ERSE CABLU RE-2Y(ST)YSWAY-FL (MULTIPAIR) 20 X 2 X 1.5, ERSE

Construc?ie

1. CONDUCTOR IEC-60228, VDE 0295, EN 60228
2. IZOLARE EN 50290-2-23 PE COMPONENTE
3. Cod culoare BS-5308 PARTEA-1 sau negru-alb;
Fiecare pereche numerotate
4. E?uare luate dou? câte dou? perechi, ECRANATE în straturi
- 1 NUM?R COMMUNICATION CORE
5. Placarea cu band? de PES
6. GENERAL SCREEN cupru cositorit DRAIN fir; TAPE AL-PES
7. INNER MANTAUA EN 50290-2-22 PVC combinate
8. Armour GALVANIZAT sârme de o?el ROTUNDE
9. MANTAUA EN 50290-2-22 PVC combinate
10. MANTAUA CULOARE RAL 5015 * BLUE; RAL 9005 * BLACK

cei care nu

CEM bune * CARACTERISTICI

Raza de îndoire MICI

FLEXIBIL

RETARDANT flac?r? ?i

REZISTENT LA HIDROCARBURI

Caracteristici tehnice

1. Rezisten?a conductorului (MAX) $0.50 \text{ mm}^2 = 36 \Omega / \text{km}$
 $0,75 \text{ mm}^2 = 24.5 \Omega / \text{km}$
 $1,0 \text{ mm}^2 = 18.1 \Omega / \text{km}$
 $1.30 \text{ mm}^2 = 13.9 \Omega / \text{km}$
 $1,5 \text{ mm}^2 = 12.1 \Omega / \text{km}$
2. Rezisten?a de izola?ie (MIN) $5000 \text{ M}\Omega \text{Km}$
3. CAPACITATE MUTUAL (MAX) $0.50 \text{ mm}^2 = 65 \text{ pF} / \text{m}$
 $0,75 \text{ mm}^2 = 65 \text{ pF} / \text{m}$
 $1,0 \text{ mm}^2 = 65 \text{ pF} / \text{m}$
 $1.30 \text{ mm}^2 = 75 \text{ pF} / \text{m}$
 $1,5 \text{ mm}^2 = 75 \text{ pF} / \text{m}$
4. Gam? de temperatur? - $30^\circ \text{C} \sim +70^\circ \text{C}$ (de stabilire a fixe)
5. FLACARA TEST IEC 60332-3-24; VDE 0482-266-2-4
RO 50266-2-4/BS EN 50266-2-4
6. L / R (raport) (MAX) $0.50 \text{ mm}^2 = 25 \text{ mH} / \Omega$
 $0,75 \text{ mm}^2 = 25 \text{ mH} / \Omega$
 $1,0 \text{ mm}^2 = 25 \text{ mH} / \Omega$
 $1.30 \text{ mm}^2 = 40 \text{ mH} / \Omega$
 $1.50 \text{ mm}^2 = 40 \text{ mH} / \Omega$
7. Curentul de sarcin? (250C) $0.50 \text{ mm}^2 = 6,0 \text{ A}$
 $0,75 \text{ mm}^2 = 13 \text{ A}$
 $1,0 \text{ mm}^2 = 16 \text{ A}$
 $1,30 \text{ mm}^2 = 18 \text{ A}$
 $1,50 \text{ mm}^2 = 20 \text{ A}$
8. Tensiunea de lucru 300/500 V.
9. TEST VOLTAJGE Core / Core = 2,000 V.
Core / Ecran = 2,000 V.
10. Îndoire 10X cablu Ø

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/cablu-re-2y-st-ysway-fl-multipair-20-x-2-x-1-5-erse>

