

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

ERSE CABLU RE-2X(ST)YSWAY-FL TIMF 8 X 3 X 1.5, ERSE

Construc?ie

1. CONDUCTOR IEC-60228, VDE 0295, EN 60228
2. IZOLARE EN 50290-2-29 XLPE
3. Cod culoare BS-5308 PARTEA-1 sau negru-alb ?i ro?u;
4. INDIVIDUAL SCREEN PSE TAPE, cupru cositorit DRAIN WIRE TAPE AL-PES
7. GENERAL SCREEN cupru cositorit DRAIN fir; TAPE AL-PES
8. INNER MANTAU A EN 50290-2-22 PVC combinate
9. Armour GALVANIZAT sârme de o?el ROTUNDE
10. MANTAU A EN 50290-2-22 PVC combinate
11. MANTAU A CULOARE RAL 5015 * BLUE; RAL 9005 * BLACK

CARACTERISTICI

- RETARDANT flac?r? ?i
- REZISTENT LA HIDROCARBURI
- POTRIVIT PENTRU Burry LA SUBTERANE
- FI * = FLAME RETARDANT manta exterioara
- RAL 5015 MANTA BLUE *: conexiunilor EX-Proof
- IN explozive ?i IN FLAMMABLE
- MEDIU.
- RAL 9005 BLACK MANTA *: Locuri in care rezistenta UV

ESTE NECESAR?

Caracteristici tehnice

1. Rezisten?a conductorului 0,50 mm² = 36 OHM / km
- 0,75 mm² = 24.5 OHM / km
- 1,0 mm² = 18.1 OHM / km
- 1.30 mm² = 13.9 OHM / km
- 1,5 mm² = 12.1 OHM / km
2. Rezisten?a de izola?ie (MIN) 5000 m OHMxKm
3. CAPACITATE MUTUAL (MAX) 0,50 mm² = 100 pF / m
- 0,75 mm² = 100 pF / m
- 1,0 mm² = 100 pF / m
- 1,30 mm² = 100 pF / m
- 1,5 mm² = 100 pF / m
4. Gam? de temperatur? - 3 ° C ~ +9 ° C (de stabilire a fixe)
5. FLACARA TEST IEC 60332-3-24; VDE 0482-266-2-4
- RO 50266-2-4/BS EN 50266-2-4
6. L / R (raport) (MAX 0,50 mm² = 25 mH / OHM
- 0,75 mm² = 25 mH / OHM
- 1,0 mm² = 25 mH / OHM
- 1.30 mm² = 40 mH / OHM
- 1,5 mm² = 40 mH / OHM
7. Curentul de sarcin? (25 ° C) 0.50 mm² = 6,0 A
- 0,75 mm² = 13 A
- 1,0 mm² = 16 A
- 1,30 mm² = 18 A
- 1,5 mm² = 20 A
8. Tensiunea de lucru 300/500 V.
9. TEST VOLTAJGE Core / Core = 2,000 V.
- Core / Ecran = 2,000 V.
10. Indoire 10X cablu Ø

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/cablu-re-2x-st-ysway-fl-timf-8-x-3-x-1-5-erse>

