

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

LEGRAND STRAIGHT LENGHT MS63 63A 2+2 OUTLETS - 2M



Caracteristici tehnice

Straight elements

MS63 (63A)

L : 2 m

Outlets : 2+2

Caracteristici generale

MS mini busbars - trunking components

Reference standard: IEC 61439-6

Reference temperature: 40 °C

Degree of Protection: IP 40/55

Thickness: 0.8 mm

Dimension: 39x97mm

N° of conductors: 4 with equal section 3P+N

Conducting «fire retardant» in accordance with EN 60332-3

Separation between the conductors by plastic insulators reinforced with 20% glass fiber, which guarantees a degree of V1 self-extinguishing (according to UL94) and conform to the glow-wire test according to IEC 60695-2-10

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/straight-lenght-ms63-63a-2-2-outlets-2m-235902>