

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**GEWISS PROIECTOR LED TIP SMART [PRO] 2.0 - 2 MODULE -
DIMABIL 1-10 V - SYMMETRICAL S2 - 5700K (CRI 70) - IP66 -
PROTECTION CLASS I**

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Sport, Big Areas
OpticĂf - S2 - Symmetric Medium
Luminaire - LED luminaire with small, mid and high lumen power
Unified Glare Rating - G*6 - ULOR = 0
AplicaĂie - Intern / Extern
LuminĂf ieĂire (lm) - 40600
Unique digital code (Datamatrix) - Currently not present
Efficiency
(lm/W) - 123
Culoare - Gri grafit
Culoare TemperaturĂf - 5700 K
Tip sursĂf de luminĂf - LED - Neinlocuibil
Color Rendering Index - CRI>70
Puterea sistemului - 330 W
Standard Deviation Colour Matching - SDCM = 5
LED Lifetime - L90B10(Tq25°C)=40.000h; L80B10(Tq25°C)=90.000h
Photobiological Risk Class - -
Greutate (Kg) - 13
Standard - EN60598-1; EN60598-2-5; IEC 62778; IEC 62471; EN13201
GaranĂie - 5 ani
ELECTRICAL AND LIGHTING FEATURES - -
TemperaturĂf de stocare - -
Tensiune de alimentare - 220 - 240 V
Operating temperature - -30 +50 °C
FrecvenĂf nominalĂf (Hz) - 50 / 60
MATERIALS - -
Driver - Included
Body - Aluminiu turnat
Driver failure rate - F10 = 80.000h Tq25°C
Ecran - Flat tempered glass 4mm
Overvoltage protection - DM 5KV / CM 10KV
Optic - Polished anodised aluminum reflector with 99.99% pure aluminum
Control System - Autonom - 1/10V
Gasket - Anti-aging silicone
INSTALLATION AND MAINTENANCE - -
Locking Hook - Hexagonal metric screws
Mounting and installation - High-mast lighting - Wall mounting - Ground mounting
External screw - Stainless steel
Tilt - Rotation on bracket with integrated goniometer
Colour - Polyester powder coated
Wiring - Watertight connector
STANDARDS AND APPROVALS - -
Prindere - ConsolĂf
Clasificare - -
Optic Maintenance - Not available
Dispozitiv cu temperaturĂf la suprafaĂf redusĂf - Nu
LED Maintenance - Not available
Certificare DIN 18032-3 - Da
Driver Box - Integrat
IPEA - -
SuprafaĂf maximĂf expusĂf la vant - 0,170 m2
ClasĂf izolaĂie - I
- - -
ClasĂf de protecĂie IP - IP66
- - -
Cod IK - IK08
- - -
Glow Test conductori - -
- - -
Ware number - 94054010
Pret: 3 817,56 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/proiector-led-tip-smart-pro-2-0-2-module-dimabil-1-10-v-symmetrical-s2-5700k-cri-70-ip66-protection-class-i-215490>