

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



GEWISS PROIECTOR LED TIP SMART [PRO] 2.0 - 3X2 MODULE - S2
SYMMETRICAL - 4000K CRI>80 - IP66 - CLASS I

GENERAL INFORMATION - -

OPTIC AND ILLUMINATING FEATURES - -

Context - Sport, Big Areas

Optic - S2 - Symmetric Medium

Luminaire - LED luminaire with mid and high lumen power

Unified Glare Rating - G*6 - ULOR = 0

Aplicatie - Intern / Extern

Luminanta (lm) - 113700

Unique digital code (Datamatrix) - Currently not present

Efficiency

(lm/W) - 117

Culoare - Gri grafit

Culoare Temperatur - 4000 K

Tip sursă de lumină - LED - Neînlocuibil

Color Rendering Index - CRI>80

Puterea sistemului - 970 W

Standard Deviation Colour Matching - SDCM = 3

LED Lifetime - L90B10(Tq25°C)=40.000h; L80B10(Tq25°C)=90.000h

Photobiological Risk Class - -

Greutate (Kg) - 29

Standard - EN60598-1; EN60598-2-5; IEC 62778; IEC 62471; EN13201

Garanție - 5 ani

ELECTRICAL AND LIGHTING FEATURES - -

Temperatură de stocare - -

Tensiune de alimentare - -

Operating temperature - -30 +50 °C

Frecvență nominală (Hz) - -

MATERIALS - -

Driver - To be ordered separately

Body - Aluminiu turnat

Driver failure rate - See external supply unit

Ecran - Flat tempered glass 4mm

Overvoltage protection - See external supply unit

Optic - Polished anodised aluminum reflector with 99.99% pure aluminum

Control System - See external supply unit

Gasket - Anti-aging silicone

INSTALLATION AND MAINTENANCE - -

Locking Hook - Hexagonal metric screws

Mouting and installation - High-mast lighting - Wall mounting - Ground mouting

External screw - Stainless steel

Tilt - Rotation on bracket with integrated goniometer

Colour - Polyester powder coated

Wiring - Watertight connector

STANDARDS AND APPROVALS - -

Prindere - Consolă

Clasificare - -

Optic Maintenance - Not available

Dispozitiv cu temperatură la suprafață redusă - Nu

LED Maintenance - Da

Certificare DIN 18032-3 - -

Driver Box - Exterior

IPEA - -

Suprafață maximă expusă la vant - 0,333 m2

Clasă izolație - I

- - -

Clasă de protecție IP - IP66

- - -

Cod IK - IK08

- - -

Glow Test conductori - -

- - -

Ware number - 94054010

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/proiector-led-tip-smart-pro-2-0-3x2-module-s2-symmetrical-4000k-cri-80-ip66-class-i-215629>