

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

GEWISS ELIA WL - EMERGENCY - 1200MM - IP54 - CLASS I



GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Lighting of warehouses, indoor parking and industrial production rooms
Optic - Wide opal
Luminaire - LED luminaire with high lumen power
Unified Glare Rating - -
Aplicatie - Intern
Lumen
output (lm) - 4500 (450 Em.)
Unique digital code (Datamatrix) - Currently not present
Efficiency
(lm/W) - 107
Culoare - Alb
Culoare Temperatur - 4000 K
Tip sursă de lumină - LED - Neînlocuibil
Color Rendering Index - CRI>80
Standard Deviation Colour Matching - SDCM = 3
LED Lifetime - L80 B50 (Tq25°) = 54.000h
Photobiological Risk Class - RG0
Greutate (Kg) - 2.7
Standard - -
Garantie - 5 ani
ELECTRICAL AND LIGHTING FEATURES - -
Temperatură de stocare - -
Tensiune de alimentare - 220 - 240 V
Operating temperature - 0 +25 °C
Frecvență nominală (Hz) - 50 / 60
MATERIALS - -
Driver - Included
Body - Polycarbonate
Driver failure rate - F05 = 50.000h Tq 25°C
Ecran - Polycarbonate
Overvoltage protection - -
Optic - -
Control System - Stand Alone - Emergency (3h)
Gasket - -
INSTALLATION AND MAINTENANCE - -
Locking Hook - -
Mounting and installation - Ceiling - Wallmounting - Suspension
External screw - -
Tilt - -
Colour - PC coloured
Wiring - Cable gland with terminal
STANDARDS AND APPROVALS - -
Prindere - -
Clasificare - -
Optic Maintenance - Not available
Dispozitiv cu temperatură la suprafață redusă - Conform
LED Maintenance - Replaceable battery
Certificare DIN 18032-3 - -
Driver Box - Integrat
IPEA - -
Suprafață maximă expusă la vânt - -
Clasă izolație - I
- - -
Clasă de protecție IP - IP66
- - -
Cod IK - IK08
- - -
Glow Test conductori - 850 °C
- - -
Ware number - 94051098
Pret: 1 689,78 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/elia-wl-emergency-1200mm-ip54-class-i-216125>