

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**GEWISS CORP DE ILUMINAT CU LED LINIAR ETANS SMART[3] PLUS
- 1600 HLO - MEDIUM BEAM TRANSPARENT DIFFUSER - ON / OFF -
CONECTOR CONEXIUNE RAPIDA - 4.000K CRI>80**

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Lighting of warehouses, indoor parking and industrial production rooms
Optic - Transparent with internal lens
Luminaire - LED fixture for general lighting
Unified Glare Rating - UGR $\leq$ 25 (4H/8H)
Aplicatie - Intern
Luminanta (lm) - 8900
Unique digital code (Datamatrix) - Datamatrix
Efficiency
(lm/W) - 146
Culoare - Gri RAL 7035
Culoare Temperatur - 4000 K
Tip sursa de luminanta - LED - Neinlocuibil
Color Rendering Index - CRI>80
Puterea sistemului - 61 W
Standard Deviation Colour Matching - SDCM = 3
LED Lifetime - L90B10(Tq25°C)=50.000h; L80B10(Tq25°C)=100.000h
Photobiological Risk Class - RG0
Greutate (Kg) - 4
Standard - EN60598-1; IEC 62778; IEC62471
Garanantie - 5 ani
ELECTRICAL AND LIGHTING FEATURES - -
Temperatur de stocare - -25 +80 °C
Tensiune de alimentare - 220-240 V
Operating temperature - -25 +50 °C
Frecventa nominala (Hz) - 50/60 Hz
MATERIALS - -
Driver - Included
Body - Polycarbonate
Driver failure rate - F10 = 100.000h Tq25°C
Ecran - UV stabilised polycarbonate
Overvoltage protection - DM 1KV / CM 2KV
Optic - PMMA lens inside
Control System - Through wiring - On/Off
Gasket - CNC deposited sealant
INSTALLATION AND MAINTENANCE - -
Locking Hook - -
Mounting and installation - Ceiling - Wallmounting - Suspension
External screw - -
Tilt - With fixing bracket
Colour - RAL7035 colored PC paste
Wiring - With GW connect watertight connector
STANDARDS AND APPROVALS - -
Prindere - Stainless steel support
Clasificare - -
Optic Maintenance - Not available
Dispozitiv cu temperatura la suprafata redus - Da
LED Maintenance - Not available
Certificare DIN 18032-3 - Not available
Driver Box - Integrat
IPEA - -
Suprafata maxima expusa la vant - -
Clasifica izolare - II
- - -
Clasifica de protectie IP - IP66/IP69
- - -
Cod IK - IK08
- - -
Glow Test conductori - 850 °C
- - -
Ware number - 94051040
Pret: 886,12 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/corp-de-iluminat-cu-led-liniar-etans-smart-3-plus-1600-hlo-medium-beam-transparent-diffuser-on-off-conector-conexiune-rapida-4-000k-cri-80-216505>