

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**GEWISS CORP DE ILUMINAT CU LED SMART [4] - HT - 1 MODUL -
STAND ALONE - ON / OFF - ELLIPTICAL OPTIC - 5700 K - IP66 -
CLASS I**

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Logistics and industrial manufacturing lighting
Optic - Elliptic
Luminaire - LED Industrial Reflector
Unified Glare Rating - -
Application - Internal
Luminous flux (lm) - 6300
Unique digital code (Datamatrix) - Datamatrix
Efficiency
(lm/W) - 131
Colour - RAL 7035
Colour Temperature - 5700 K
Type of light source - LED - Non-replaceable
Colour Rendering Index - CRI>80
Power of the system - 48 W
Standard Deviation Colour Matching - SDCM = 3
LED Lifetime - L90B10(Tq25°C)>150.000h; L90B10(Tq60°C)=60.000h
Photobiological Risk Class - RG0
Weight (Kg) - 3.5
Standard - EN 60598-1 ; EN 60598-2-1 ; EN 60598-2-24
Warranty - 5 ani
ELECTRICAL AND LIGHTING FEATURES - -
Storage temperature - -40 +70 °C
Supply voltage - 220 - 240 V
Operating temperature - -30°C ÷ +60 °C
Nominal frequency (Hz) - 50/60 Hz
MATERIALS - -
Driver - Included
Body - PA6 "Halogen Free" loaded fibreglass
Driver failure rate - F10=100.000h Tq25°C/50.000h Tq60°C
Lens - Tempered glass Thickness 4mm
Overvoltage protection - DM 6 kV / CM 10 kV
Optic - Metallic PC reflector and PMMA lenses
Control System - ON / OFF
Gasket - anti-aging silicone
INSTALLATION AND MAINTENANCE - -
Locking Hook - -
Mounting and installation - Ceiling - Wallmounting - Suspension
External screw - O-ring
Tilt - With bracket accessory
Colour - RAL 7035
Wiring - With GW connect watertight connector
STANDARDS AND APPROVALS - -
Principles - -
Classification - -
Optic Maintenance - Non-replaceable
Device with temperature at the surface of the reduced - Da
LED Maintenance - Non-replaceable
Certification DIN 18032-3 - -
Driver Box - Integrated
IPEA - -
Maximum exposed surface area - 0,097 m²
Classification - I
- - -
Protection class IP - IP66
- - -
Code IK - IK08
- - -
Glow Test conductor - 850 °C
- - -
Ware number - 94051098
Price: 1 585,48 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-de-iluminat-cu-led-smart-4-ht-1-modul-stand-alone-on-off-elliptical-optic-5700-k-ip66-class-i-216671>