

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**GEWISS CORP DE ILUMINAT CU LED SMART [4] - HLO - 2 MODULE -
THROUGH WIRING - ON / OFF - ELLIPTICAL OPTIC - 3000 K - IP66 -
CLASS I**

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Lighting for industries and sports facilities
Optic - Eliptic
Luminaire - LED Industrial Reflector
Unified Glare Rating - -
Aplicatie - Intern
Luminanta (lm) - 15300
Unique digital code (Datamatrix) - Datamatrix
Efficiency
(lm/W) - 122
Culoare - Gri RAL 7035
Culoare Temperatur - 3000 K
Tip sursa de lumina - LED - Neinlocuibil
Color Rendering Index - CRI>80
Puterea sistemului - 125 W
Standard Deviation Colour Matching - SDCM = 3
LED Lifetime - L90B10(Tq25°C)>150.000h; L90B10(Tq50°C)=100.000h
Photobiological Risk Class - RG0
Greutate (Kg) - 6.5
Standard - EN 60598-1 ; EN 60598-2-1 ; EN 60598-2-24
Garantie - 5 ani
ELECTRICAL AND LIGHTING FEATURES - -
Temperatur de stocare - -40 +70 °C
Tensiune de alimentare - 220 - 240 V
Operating temperature - -30°C ÷ +50 °C
Frecventa nominala (Hz) - 50/60 Hz
MATERIALS - -
Driver - Included
Body - PA6 "Halogen Free" loaded fibreglass
Driver failure rate - F10 = 70.000h Tq25°C/35.000h Tq50°C
Ecran - Tempered glass Thickness 4mm
Overvoltage protection - DM 6kV / CM 6kV
Optic - Metallic PC reflector and PMMA lenses
Control System - ON / OFF
Gasket - anti-aging silicone
INSTALLATION AND MAINTENANCE - -
Locking Hook - -
Mounting and installation - Ceiling - Wallmounting - Suspension
External screw - Otel
Tilt - With bracket accessory
Colour - Gri RAL 7035
Wiring - With GW connect watertight connector
STANDARDS AND APPROVALS - -
Prindere - -
Clasificare - -
Optic Maintenance - Non-replaceable
Dispozitiv cu temperatura la suprafata redus - Da
LED Maintenance - Non-replaceable
Certificare DIN 18032-3 - With Bracket - Rope Kit + terminal (in approval)
Driver Box - Integrat
IPEA - -
Suprafata maxima expusa la vant - 0,184 m²
Clasa izolatie - I
- - -
Clasa de protectie IP - IP66
- - -
Cod IK - IK08
- - -
Glow Test conductori - 850 °C
- - -
Ware number - 94051098
Pret: 2 467,21 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/corp-de-iluminat-cu-led-smart-4-hlo-2-module-through-wiring-on-off-elliptical-optic-3000-k-ip66-class-i-217071>