



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410





Caracteristici tehnice 19" - PDU Basic IEC 60320 standard Connection on terminal block (except Cat.No 6 468 15) 6 C19 outlets with cord locking system

Caracteristici generale Legrand cabling system LCS³ energy Distribution - horizontal (1U/2U) Basic Putere

Distribution Units (PDU)

To provide ~ electric Putere for IT equipment in 19" enclosures 230 V - 50/60 Hz Tensiune de alimentare

1U aluminium profile

End cap with metallic brackets and cable holder shape Quick fixing (no screws) on 19" fixing centers. Can also be installed vertically by

reverting the brackets (no screws)

2P+E outlets:

C13 and C19 standard outlets are equipped with cord locking system to avoid any accidental disconnection. Universal solution compatible with all the cords (C14 plugs for C13 and C20 plugs for C19)

French, German and British standard outlets are equipped with safety shutters French and German standard outlets are inclined at 55°

Black module (outlets and functions) Pret: 255,51 lei (TVA inclus)

 $\begin{tabular}{ll} \textbf{Detalii online:} & \textbf{https://www.materialeelectrice.ro/set-prize-} 19-pdu-lcs3-1-u-6-x-c19-iec-60320-standard-221764 \end{tabular}$