

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**LEGRAND BRITISH STANDARD RCD SYNERGY -ELO DOI POLI 30 MA
2 MODULE -13 A -250 V~ -AUTHENTIC POLISHED STAINLESS STEEL**

Caracteristici tehnice
RCD sockets 13 A - 250 V~
Conform to BS 7288: 1990 and BS 1363 - Part 2: 1995
Conventional earth pin release shutter
Maximum operating current 16 A
Electronic RCD module with a membrane switch for "test and reset"
Flush mounting back box : min. 25 mm deep
ELO - DP 30 mA - 2 gang
Trips in the event of a Putere failure
Ideal for applications where it is desirable to prevent automatic reactivation of
equipment after a Putere failure
For hazardous, e.g. machinery, Putere tools
Nominal plate dimensions: 86 x 146 mm
Polished stainless steel
Caracteristici generale
Synergy™ - British standard RCD sockets - Authentic
Slim front plate:
BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L
PSS: Plates made of Stainless Steel + rust resistance
GG: Plates made of Stainless Steel + rust resistance
Terminal screws captive and backed off ready for cabling - large angled terminal entries
Compact mechanism for maximum wiring space
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/british-standard-rcd-synergy-elo-doi-poli-30-ma-2-module-13-a-250-v-authentic-polished-stainless-steel-223304>